Product data sheet

Specifications





EtherNet/IP communication card - 2 RJ 45 connectors

VW3A3320

- Discontinued on: Jan 23, 2021
- ! To be end-of-service on: Jan 24, 2026

① Discontinued - Service only

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product or Component Type	Communication card
Range Compatibility	Altivar 71 Altivar 61
Communication Port Protocol	EtherNet/IP Modbus TCP
Connector Type	2 RJ45 connectors
Transmission Rate	10/100 Mbps
Physical interface	IEEE 802.3 Ethernet IP/Modbus TCP
Web services	Altivar viewer Drive parameters Ethernet/IP scanner setup FDR Agent Data editor E-mail Security Modbus TCP scanner setup Altivar chart Drive monitor Ethernet/IP setup Drive recorder Ethernet statistics Message statistics

Complementary

Exchange mode	Half duplex and full duplex
Communication data link	MAC : IEEE 802.3 LLC : IEEE 802.2
Communication network type	IP RFC791 ICMP
Communication transport type	UDP TCP RFC793
Web server	Embedded

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Communication service	CiA 402 profile		
	I/O profile		
	CIP AC Drive (02) profile		
	Diagnostics (08)		
	FTP		
	Read holding registers (03) Read input registers (04) Read/write multiple registers (23) SNMP TFTP Write multiple registers (16) Write single register (06)		
		Ethernet/IP adapter	
		Read device identification (43/14)	
		Display type	1 LED Link (Link Status)
			1 LED MS (Module Status)
			1 LED NS (Network Status)
			1 LED TX/RX (Transmit/Receive port 1)
	1 LED TX/RX (Transmit/Receive port 2)		
	Graphic display terminal control word received		
Graphic display terminal number of frames received			
Graphic display terminal reference received			
Net Weight	0.7 lb(US) (0.3 kg)		

Ordering and shipping details

Category	US1CP4C22135
Discount Schedule	CP4C
GTIN	3606480612978
Returnability	No
Country of origin	US

Packing Units

PCE
1
2.992 in (7.600 cm)
6.890 in (17.500 cm)
9.252 in (23.500 cm)
9.912 oz (281.000 g)
S03
7
11.811 in (30.000 cm)
11.811 in (30.000 cm)
15.748 in (40.000 cm)
5.406 lb(US) (2.452 kg)
P06
28
17.717 in (45.000 cm)
23.622 in (60.000 cm)
31.496 in (80.000 cm)
30.441 lb(US) (13.808 kg)



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov