Product data sheet

Specifications





Altivar

communication module EtherNet IP Modbus TCP, 10 or 100Mbps, 2 x RJ45 connectors

VW3A3720

Product availability: Stock - Normally stocked in distribution facility

Price*: 330.00 USD

Main

Range of Product

age e eauet	Autval
Product or Component Type	Communication module
Complementary	
Range compatibility	Altivar Process ATV600 Altivar Process Modular
Communication Port Protocol	Modbus TCP EtherNet/IP
Electrical connection	2 connectors RJ45, Ethernet IP/Modbus TCP
Transmission Rate	10/100 Mbps
Exchange mode	Half duplex and full duplex
Communication service	SNMP agent Ethernet IP Modbus TCP server Ethernet IP/Modbus TCP Ethernet/IP adapter Ethernet IP RSTP support Ethernet IP FTP Ethernet IP ODVA AC drive and CiA 402 profile Ethernet IP/Modbus TCP Auto-MDIX Ethernet IP/Modbus TCP 32 parameters IN - 32 parameters OUT implicit messaging Ethernet IP/Modbus TCP FDR Ethernet IP/Modbus TCP
Communication Network Type	IPv6 (internet protocol)
Topology	Daisy chain
Time synchronisation protocol	SNTP
Web server	Embedded HTTP server
Web services	Save/restore drive configuration Drive setting and diagnostic Energy monitoring Widgets (ID, control, data table, diagnostic, charts) Upgrade drive firmware Customizable home page Drive monitor Pump function setting and monitoring Ethernet setting and diagnostic
Display type	1 LED MS (Module Status) 1 LED NS (Network Status) 1 LED TX/RX (Transmit/Receive port 1) 1 LED TX/RX (Transmit/Receive port 2)
Bus profile	CIP AC Drive CiA 402
Net Weight	0.4 lb(US) (0.2 kg)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Product certifications ODVA
Achilles level 2

Ordering and shipping details

Category	US1CP4E22276
Discount Schedule	CP4E
GTIN	3606480702549
Returnability	Yes
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.638 in (6.700 cm)
Package 1 Width	5.118 in (13.000 cm)
Package 1 Length	7.402 in (18.800 cm)
Package 1 Weight	5.503 oz (156.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	16
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	7.253 lb(US) (3.290 kg)



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov