

braking resistor, Altivar, IP20, 100hm, 1000W

VW3A7705

! Discontinued on: 20 May 2021

! Discontinued

Main

Range of product	Altivar	
Range compatibility	Altivar 312	
	Lexium 32i	
	Lexium 52	
	Lexium 32	
	Altivar 61	
Product compatibility	LXM32MC10N4	
	LXM32MD85N4	
	ATV312HD11M3	
	ATV312HD15M3	
	ATV61HD11M3X	
	ATV61HD37N4	
	ATV61HD55Y	
	ATV61HD75Y	
	ATV61WD45N4	
	ATV61WD45N4C	
	ATV71HD11M3X	
	ATV71HD37N4	
	ATV71HD45Y	
	ATV71HD55Y	
	ATV71WD37N4	
ohmic value	10 Ohm	
[Ue] rated operational voltage	24 V DC at 0.1 A	
	250 V AC at 1 A	

Complementary

Average power available	1 kW at 50 °C 1.15 kW at 40 °C	
Continuous power	1000 W	
Electrical connection	M6 bar wire for drive terminal, connection capacity: <= 2.5 mm² / AWG 14 for temperature control switch	
temperature controlled switch contact resistance	60 μOhm	
Protection type	Thermal protection via drive or temperature control switch at 120 °C	
Width	240 mm	
Height	484 mm	
Depth	301 mm	
net weight	11 kg	

Environment

IP degree of protection	IP20
Ambient air temperature for storage	-2570 °C

Ambient air temperature for 0...50 °C operation

Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	33.200 cm
Package 1 Width	40.800 cm
Package 1 Length	57.600 cm
Package 1 Weight	9.648 kg
Unit Type of Package 2	P12
Number of Units in Package 2	6
Package 2 Height	97.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	72.000 kg

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
	Mercury Free	
⊘	Rohs Exemption Information	Yes
Rea	ch Regulation	REACh Declaration
Eu F	Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Chir	na Rohs Regulation	China RoHS declaration

Dimensions Drawings

Braking Resistor

Dimensions

