



power cable - between servomotor BSH and servodrive - 4 x 4 mm² + 2 x 1 mm² -75m

VW3M5103R750

! Discontinued on: 30 Jun 2023

(!) Discontinued

Main

Product or component type	Power cable	
accessory / separate part type	Preassembled power cordset	
Accessory / separate part category	Connection accessory	
Product compatibility	Servo motor BMH, 1 motor stacks (190 mm) mounting type E conforming to EN 60204-1	
	Servo motor BMH, 3 motor stacks (205 mm) mounting type E conforming to EN 60204-1	
	Servo motor BSH, 2 motor stacks (140 mm)	
	Servo motor BSH, 3 motor stacks (140 mm)	
	Servo motor BSH, 4 motor stacks (140 mm)	
Accessory / separate part destination	Between servo motor and servo drive	
Range compatibility	Lexium 15	
	Lexium 05	
	Lexium 32	
Cable length	75 m	
Cable composition	4 x 4 mm² + 2 x 1 mm²	

Complementary

Electrical connection	Free end for servo drive side Connector - industrial M40 for servo motor side
Product weight	45 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.0 cm
Package 1 Width	60.0 cm
Package 1 Length	60.0 cm
Package 1 Weight	33.1 kg

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
Ø	Toxic Heavy Metal Free	
⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information