



power cable - between servomotor BSH and servodrive - 4 x 6 mm² + 2 x 1 mm² -25m

VW3M5105R250

Main

Product or component type	Power cable	
accessory / separate part type	Preassembled power cordset Connection accessory	
Accessory / separate part category		
Product compatibility	Servo motor BMH, 1 motor stacks (190 mm) mounting type B2 conforming to EN 60204-1	
	Servo motor BMH, 2 motor stacks (190 mm) mounting type E conforming to EN 60204-1	
	Servo motor BMH, 3 motor stacks (190 mm) mounting type E conforming to EN 60204-1	
	Servo motor BMH, 3 motor stacks (205 mm) mounting type B2 conforming to EN 60204-1	
Accessory / separate part destination	Between servo motor and servo drive	
Range compatibility	Lexium 32	
Cable length	25 m	
Cable composition	4 x 6 mm² + 2 x 1 mm²	

Complementary

Electrical connection	Free end for servo drive side Connector - industrial M40 for servo motor side	
Product weight	15.5 kg	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.0 cm
Package 1 Width	30.0 cm
Package 1 Length	43.0 cm
Package 1 Weight	17.26 kg

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
Ø	Toxic Heavy Metal Free	
⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information