# **Product datasheet**

Specifications



power cable 1,5m shielded 4x 0,82mm<sup>2</sup>, BCH2 leads connection

VW3M5D1AR15

#### Main

Lexium 28
Power cable
Preassembled power cordset
Connection accessory
Servo motor BCH2 at 50 W (40 mm) (without brake) Servo motor BCH2 at 100 W (40 mm) (without brake) Servo motor BCH2 at 200 W (60 mm) (without brake) Servo motor BCH2 at 400 W (60 mm) (without brake) Servo motor BCH2 at 400 W (80 mm) (without brake) Servo motor BCH2 at 750 W (80 mm) (without brake)
Between servo motor and servo drive
Lexium 28
1.5 m

## Complementary

Electrical connection	Free end for servo drive side Connector - Molex 4-pin for servo motor side
AWG gauge	4 x AWG 18
Net weight	0.2 kg

## **Packing Units**

PCE
1
2.0 cm
29.0 cm
36.0 cm
211.0 g
S02
10
15.0 cm
30.0 cm
40.0 cm
2.422 kg

### **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

#### Well-being performance

	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	Yes
	Pvc Free	
Read	ch Regulation	REACh Declaration
Eu F	Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Chin	a Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)