# **Product datasheet**

Specifications



# power cable 5m shielded 4x 6mm<sup>2</sup>, BCH2 MIL connector

VW3M5D6AR50

### Main

Lexium 28
Power cable
Preassembled power cordset
Connection accessory
Servo motor BCH2 at 3000 W (180 mm) (without brake) Servo motor BCH2 at 3500 W (180 mm) (without brake) Servo motor BCH2 at 4500 W (180 mm) (without brake)
Between servo motor and servo drive
Lexium 28
5 m

## Complementary

Electrical connection	Free end for servo drive side Connector - MIL big for servo motor side
AWG gauge	4 x AWG 10
Net weight	3.4 kg

# **Packing Units**

PCE
1
9.000 cm
39.000 cm
39.000 cm
2.548 kg
S04
5
30.000 cm
40.000 cm
60.000 cm
13.570 kg

### **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

#### Well-being performance

Chin	a Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Eu F	Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Read	ch Regulation	REACh Declaration
	Pvc Free	
	Rohs Exemption Information	Yes
	Mercury Free	
	Toxic Heavy Metal Free	
	Reach Free Of Svhc	