

Product datasheet

Specifications



encoder cable 3m shielded, leads connection for BCH2.B/.D/.F, CN2 plug

VW3M8D1AR30

Main

Range of product	Lexium
Accessory / separate part categor	Connection accessory
accessory / separate part type	Encoder cable
product or component type	Encoder cable
Device application	For BCH2 with SinCos single turn encoder
Accessory / separate part destination	From servo motor to servo drive
Cable composition	5 x (2 x 0.13 mm²)

Complementary

Electrical connection	1 connector Firewire 6 pin(s) 1 connector Molex 9 pin(s)
Range compatibility	Lexium 28
Cable length	3 m
net weight	1 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.000 cm
Package 1 Width	29.000 cm
Package 1 Length	25.000 cm
Package 1 Weight	134.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	1.715 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)

Well-being performance

✓	Reach Free Of Svhc	
✓	Toxic Heavy Metal Free	
✓	Mercury Free	
✓	Rohs Exemption Information	Yes
✓	Pvc Free	
Reach Regulation	REACH Declaration	
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	