Product data sheet

Specifications





Auxiliary contact block,TeSys Control,1 NC early break,for VN12,VN20

VZN06

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 40.50 USD

Main

Range	TeSys
Device short name	VZN
Product or Component Type	Auxiliary contact block
Performance level	Standard
Contacts type and composition	1 NC
Contact operation	Early-break
Product Compatibility	VN12 VN20
Mounting Location	Left Right

Complementary

Range compatibility	TeSys TeSys VARIO VCFN switch disconnector
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	6 kV
[Ith] conventional free air thermal current	6 A
[Ithe] conventional enclosed thermal current	4 A
Mechanical durability	50000 cycles
Electrical durability	30000 cycles DC-11 50000 cycles AC-21
Connections - terminals	screw clamp terminals 2 0.0010.002 in ² (0.751.5 mm ²) flexible - with cable end screw clamp terminals 2 0.0020.004 in ² (12.5 mm ²) solid
Tightening torque	6.2 lbf.in (0.7 N.m) screw clamp terminals
Height	1.8 in (45.5 mm)
Width	0.5 in (12 mm)
Depth	1.5 in (39 mm)
Net Weight	0.04 lb(US) (0.02 kg)

Environment

Standards	IEC 60947-5
Product Certifications	CSA GL UL

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Protective treatment	тс
IP degree of protection	IP20 conforming to IEC 60529
Ambient Air Temperature for Operation	-4122 °F (-2050 °C)
Fire resistance	1760 °F (960 °C) IEC 60695-2-1

Ordering and shipping details

Category	US10CP121730
Discount Schedule	0CP1
GTIN	3389110760064
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.9 in (2.2 cm)
Package 1 Width	3.1 in (8.0 cm)
Package 1 Length	3.8 in (9.6 cm)
Package 1 Weight	0.7 oz (20.0 g)
Unit Type of Package 2	S01
Number of Units in Package 2	40
Package 2 Height	5.9 in (15.0 cm)
Package 2 Width	5.9 in (15.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	2.47 lb(US) (1.12 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations