# Product data sheet

Specifications

## Head for push button, Harmony XAC, plastic, black, booted, operating travel 4mm

XACB9122

---

**Product availability: Stock - Normally stocked in distribution facility**

## Price*: 16.40 USD

## Main

| | |
|---|---|
| **Range Of Product** | Harmony XAC |
| **Product Or Component Type** | Head for push-button |
| **Component Name** | XACB |
| **Marking** | Unmarked |
| **Operator Additional Information** | Booted |
| **Operating Travel** | 0.16 in (4 mm) |
| **Cap/Operator Or Lens Colour** | Black |
| **Product Compatibility** | XENC....<br>XESD2251<br>XESB2011<br>XENB....<br>XESD2241<br>XESD2201<br>XEND.... |
| **Sale Per Indivisible Quantity** | 10 |

## Complementary

| | |
|---|---|
| **Net Weight** | 0.01 lb(US) (0.005 kg) |

## Environment

| | |
|---|---|
| **Standards** | IEC 60947-5-1<br>CSA C22.2 No 14<br>EN 60947-5-1 |
| **Ambient Air Temperature For Operation** | -40…158 °F (-40…70 °C) |
| **Ambient Air Temperature For Storage** | -40…158 °F (-40…70 °C) |
| **Vibration Resistance** | 15 gn 10…500 Hz)IEC 60068-2-6 |
| **Shock Resistance** | 100 gn IEC 60068-2-27 |
| **Electrical Shock Protection Class** | Class II IEC 61140 |
| **Ip Degree Of Protection** | IP65 conforming to IEC 60529 |
| **Ik Degree Of Protection** | IK08 conforming to EN 50102 |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US10CS222473 |
| **Discount Schedule** | 0CS2 |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| | |
|---|---|
| **Gtin** | 3389110644609 |
| **Returnability** | Yes |
| **Country Of Origin** | FR |

## Packing Units

| | |
|---|---|
| **Unit Type Of Package 1** | PCE |
| **Number Of Units In Package 1** | 1 |
| **Package 1 Height** | 1.18 in (3.0 cm) |
| **Package 1 Width** | 4.72 in (12.0 cm) |
| **Package 1 Length** | 4.72 in (12.0 cm) |
| **Package 1 Weight** | 0.21 oz (6.0 g) |
| **Unit Type Of Package 2** | BAG |
| **Number Of Units In Package 2** | 10 |
| **Package 2 Height** | 4.72 in (12.0 cm) |
| **Package 2 Width** | 1.18 in (3.0 cm) |
| **Package 2 Length** | 4.72 in (12.0 cm) |
| **Package 2 Weight** | 2.12 oz (60.0 g) |
| **Unit Type Of Package 3** | S01 |
| **Number Of Units In Package 3** | 150 |
| **Package 3 Height** | 5.91 in (15.0 cm) |
| **Package 3 Width** | 5.91 in (15.0 cm) |
| **Package 3 Length** | 15.75 in (40.0 cm) |
| **Package 3 Weight** | 2.51 lb(US) (1.139 kg) |

## Contractual warranty

| | |
|---|---|
| **Warranty** | 18 months |

Life Is On | Schneider Electric

# Sustainability

**Green Premium$^{TM}$ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-$CO_2$ products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium ⟩

Guide to assess a product's sustainability ⟩

## Well-being performance

✅ Reach Free Of Svhc

✅ Toxic Heavy Metal Free

✅ Mercury Free

✅ Rohs Exemption Information          Yes

**Reach Regulation**          REACh Declaration

**Eu Rohs Directive**          Pro-active compliance (Product out of EU RoHS legal scope)

EU RoHS Declaration

**China Rohs Regulation**          China RoHS declaration

**California Proposition 65**          WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov