

Product data sheet

Specifications



Head for push button, Harmony XAC, plastic, white, booted, operating travel 16mm, 25...+ 70 degree C

XACB9211

Main

| | |
|---------------------------------|--|
| Range Of Product | Harmony XAC |
| Product Or Component Type | Head for push-button |
| Component Name | XACB |
| Marking | Unmarked |
| Operator Additional Information | Booted |
| Operating Travel | 0.63 in (16 mm) |
| Cap/Operator Or Lens Colour | White |
| Product Compatibility | XESD1191 XESD1291 XESD1181 XESD1281 |
| Sale Per Indivisible Quantity | 10 |

Complementary

| | |
|------------|------------------------|
| Net Weight | 0.01 lb(US) (0.005 kg) |
|------------|------------------------|

Environment

| | |
|---------------------------------------|---|
| Standards | IEC 60947-5-1 CSA C22.2 No 14 IEC 60947-5-1 |
| Ambient Air Temperature For Operation | -13...158 °F (-25...70 °C) |
| Ambient Air Temperature For Storage | -40...158 °F (-40...70 °C) |
| Vibration Resistance | 15 gn 10...500 Hz)IEC 60068-2-6 |
| Shock Resistance | 100 gn IEC 60068-2-27 |
| Electrical Shock Protection Class | Class II IEC 61140 |
| Ip Degree Of Protection | IP65 conforming to IEC 60529 |
| Ik Degree Of Protection | IK08 conforming to IEC 62262 |

Packing Units

| | |
|------------------------------|--------------------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 1.06 in (2.700 cm) |
| Package 1 Width | 1.06 in (2.700 cm) |
| Package 1 Length | 1.06 in (2.700 cm) |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|------------------------------|------------------------|
| Package 1 Weight | 0.23 oz (6.600 g) |
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 10 |
| Package 2 Height | 1.57 in (4.000 cm) |
| Package 2 Width | 3.15 in (8.000 cm) |
| Package 2 Length | 3.94 in (10.000 cm) |
| Package 2 Weight | 2.47 oz (70.000 g) |
| Unit Type Of Package 3 | S01 |
| Number Of Units In Package 3 | 150 |
| Package 3 Height | 5.91 in (15.000 cm) |
| Package 3 Width | 5.91 in (15.000 cm) |
| Package 3 Length | 15.75 in (40.000 cm) |
| Package 3 Weight | 2.67 lb(US) (1.212 kg) |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Sustainability





Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

| | | |
|---|----------------------------|---|
|  | Reach Free Of Svhc | |
|  | Toxic Heavy Metal Free | |
|  | Mercury Free | |
|  | Rohs Exemption Information | Yes |
| | | |
| Reach Regulation | | REACH Declaration |
| | | |
| Eu Rohs Directive | | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| | | |
| China Rohs Regulation | | China RoHS declaration |