Product data sheet

Specification





Die-cast empty control station, Harmony XAP, zinc alloy, grey, 5 cut-outs, 22mm 85 x 310 x 77 mm

XAPG59505

Product availability: Stock - Normally stocked in distribution facility

Price*: 268.00 USD

Main

Range Of Product	Harmony XAP	
Product Or Component Type	pe Die-cast empty control station	
Device Short Name	lame XAPG	
Product Destination	For Ø 22 mm control and signalling units	
Number Of Cut-Out	5 cut-outs	
Colour Of Base Of Enclosure	Grey RAL 7032)	
Colour Of Cover	Grey RAL 7032)	
Control Station Type	Metal	
Material	Die cast aluminium	
Sale Per Indivisible Quantity	1	
Ip Degree Of Protection	f Protection IP65 IEC 60529	
Resistance To Chemical Agents	Special treatment can be obtained on request	

Complementary

Number Of Vertical Rows	1	
Number Of Horizontal Rows	5	
Cut-Out Dimensions	Ø 22 mm	
Cable Entry	cable gland 1 x cable gland	
Thread Type	3/4 NPT	
Cad Overall Width	3.35 in (85 mm)	
Cad Overall Height	12.20 in (310 mm)	
Cad Overall Depth	3.03 in (77 mm)	
Net Weight	1.83 lb(US) (0.830 kg)	
Compatibility Code	XAPG	

Environment

Protective Treatment	TH
Ambient Air Temperature For Storage	-40158 °F (-4070 °C)
Ambient Air Temperature For Operation	-13158 °F (-2570 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Electrical Shock Protection Class	Class I IEC 60536 Class I NF C 20-030	
Ik Degree Of Protection	IK07 IFC 62262	

Ordering and shipping details

Category	US10CS222475	
Discount Schedule	0CS2	
Gtin	3389118381681	
Returnability	Yes	
Country Of Origin	FR	

Packing Units

Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Height	3.54 in (9.000 cm)	
Package 1 Width	4.84 in (12.300 cm)	
Package 1 Length	12.01 in (30.500 cm)	
Package 1 Weight	33.86 oz (960.000 g)	
Unit Type Of Package 2	S02	
Number Of Units In Package 2	3	
Package 2 Height	5.91 in (15.000 cm)	
Package 2 Width	11.81 in (30.000 cm)	
Package 2 Length	15.75 in (40.000 cm)	
Package 2 Weight	6.91 lb(US) (3.133 kg)	

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
⊘	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov