

system with charger, Harmony eXLhoist, standard, shoulder belt, cable USB/RJ45 and config software

XARSK8D18W

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1,943.00 USD

Main

Range Of Product	Harmony eXLhoist
Product Or Component Type	Control station
Device Short Name	XARS
Control Station Type	Wireless
Product Specific Application	Hoisting applications Material handling
Number Of Channels	50
Control Station Application	Stop function SIL 2 maximum can reach PL d/category 3)IEC 62061 Stop function SIL 2 maximum can reach PL d/category 3)ISO 13849-1 Emergency stop function SIL 3 maximum can reach PL e/category 4)IEC 62061 Emergency stop function SIL 3 maximum can reach PL e/category 4)ISO 13849-1 Motion function SIL 1 maximum can reach PL c/category 1)IEC 62061 Motion function SIL 1 maximum can reach PL c/category 1)ISO 13849-1 Limiter protection function SIL 1 maximum can reach PL c/category 1)IEC 62061 Limiter protection function SIL 1 maximum can reach PL c/category 1)ISO 13849-1

Complementary

Kit Composition	Remote control Base station Shoulder belt Cable Configuration software
Operating Distance	100 m in free air
Cable Entry	Cable gland
Communication Network Type	Wireless bluetooth low energy
Transmission Frequency	2.4 GHz

Environment

Radio Agreement	SRRC RSS ARIB ANATEL FCC	
Relative Humidity	095 % -4113 °F (-2045 °C) storage	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Electromagnetic Compatibility	Resistance to electrostatic discharge - test level: 4 kV class B (on contact) conforming to IEC 61000-4-2 Resistance to electrostatic discharge - test level: 8 kV class B (in air) conforming to IEC 61000-4-2 Resistance to radiated electromagnetic fields - test level: 10 V/m class B conforming to IEC 61000-4-3
Standards	IEC 60204-1 safety ISO 13849-1 safety IEC 62061 safety IEC 61508 safety IEC 61508 safety ISO 13850 safety IEC 60204-32 hoisting applications ETSI EN 301 489-1 radio ETSI EN 301 489-3 radio ETSI EN 301 489-17 radio ETSI EN 300 440-2 radio ETSI EN 300 328 radio FCC part 15 radio RSS GEN issue 3 radio RSS 210 issue 8 radio ARIB STD-T81 radio
Product Certifications	CE UL CSA C-tick JIS KC EAC

Ordering and shipping details

Category	US10CS222479
Discount Schedule	0CS2
Gtin	3606480662416
Returnability	No
Country Of Origin	US

Packing Units

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency

Well-being performance

Mercury Free	
Rohs Exemption Information	Yes
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov