# Product data sheet

Specifications



Control station, Harmony eXLhoist, standard, XARS8L12W system with charger, shoulder belt, cable USB RJ45 and config software

XARSK8L12W

Product availability: Non-Stock - Not normally stocked in distribution facility

### Price\*: 1,450.00 USD

#### Main

Range of Product	Harmony eXLhoist
Product or Component Type	Control station
Device short name	XARS
Control station type	Wireless
Product Specific Application	Material handling Hoisting applications
Number of channels	50
Control station application	Stop function SIL 2 maximum can reach PL d/category 3)IEC 62061 Stop function SIL 2 maximum can reach PL d/category 3)ISO 13849-1 Emergency stop function SIL 3 maximum can reach PL e/category 4)IEC 62061 Emergency stop function SIL 3 maximum can reach PL e/category 4)ISO 13849-1 Motion function SIL 1 maximum can reach PL c/category 1)IEC 62061 Motion function SIL 1 maximum can reach PL c/category 1)ISO 13849-1 Limiter protection function SIL 1 maximum can reach PL c/category 1)IEC 62061 Limiter protection function SIL 1 maximum can reach PL c/category 1)IEC 62061

#### Complementary

Kit composition	Cable Remote control Shoulder belt Base station Configuration software
Operating distance	100 m in free air
Cable entry	Cable gland
Communication network type	Wireless bluetooth low energy
transmission frequency	2.4 GHz

#### Environment

Radio agreement	SRRC ICASA FCC
	ARIB
	RSS
	ANATEL

Relative humidity

0...95 % -4...113 °F (-20...45 °C) storage

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Electromagnetic compatibility	Resistance to electrostatic discharge - test level: 4 kV class B (on contact) conforming to IEC 61000-4-2 Resistance to electrostatic discharge - test level: 8 kV class B (in air) conforming to IEC 61000-4-2 Resistance to radiated electromagnetic fields - test level: 10 V/m class B conforming to IEC 61000-4-3
Standards	IEC 60204-1 safety ISO 13849-1 safety IEC 62061 safety IEC 61508 safety ISO 13850 safety IEC 60204-32 hoisting applications ETSI EN 301 489-1 radio ETSI EN 301 489-3 radio ETSI EN 301 489-17 radio ETSI EN 300 440-2 radio ETSI EN 300 440-2 radio ETSI EN 300 328 radio FCC part 15 radio RSS GEN issue 3 radio RSS GEN issue 3 radio ARIB STD-T81 radio
Product certifications	CE UL CSA C-tick JIS KC EAC

## Ordering and shipping details

Category	US10CS222479
Discount Schedule	0CS2
GTIN	3606480662393
Returnability	Yes
Country of origin	FR

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.874 in (20.000 cm)
Package 1 Width	11.220 in (28.500 cm)
Package 1 Length	12.087 in (30.700 cm)
Package 1 Weight	6.678 lb(US) (3.029 kg)
Unit Type of Package 2	S04
Number of Units in Package 2	2
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	15.748 in (40.000 cm)
Package 2 Length	23.622 in (60.000 cm)
Package 2 Weight	14.551 lb(US) (6.600 kg)

#### Sustainability

**Green Premium<sup>™</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency

#### Well-being performance

Mercury Free

Rohs Exemption Information	Yes
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov