Product datasheet

Specification





Manual overload reset push button, Harmony XB5, green flush, 22mm, for 17...120 mm actuation distance

XB5AA831

Main

| Range Of Product | Harmony XB5 | |
|------------------------------|--|--|
| Product Or Component Type | onent Type Manual overload reset push-button | |
| Device Short Name | XB5 | |
| Bezel Material | Dark grey plastic | |
| Fixing Collar Material | Plastic | |
| Head Type | Standard | |
| Mounting Diamete | 22 mm | |
| Shape Of Signaling Unit Head | Round | |
| Operator Profile | Green flush, unmarked | |
| Activating Distance | 17120 mm | |
| Device Presentation | Complete product | |

Complementary

| Height | 29 mm | |
|---------------------------------------|---------------------------------------|--|
| Width | 29 mm | |
| Depth | 120 mm | |
| Net Weight | 0.027 kg | |
| Resistance To High Pressure Washer | 7000000 Pa at 55 °C, distance : 0.1 m | |
| Operating Travel | 10 mm | |

Environment

| Protective Treatment | тн |
|--|----------------------------------|
| Ambient Air Temperature For Storage | -4070 °C |
| Ambient Air Temperature For Operation | -4070 °C |
| Electrical Shock Protection Class | Class II conforming to IEC 60536 |
| Ip Degree Of Protection | IP66 conforming to IEC 60529 |
| Nema Degree Of Protection | NEMA 4X |
| Ik Degree Of Protection | IK03 conforming to IEC 50102 |
| Standards | IEC 60947-1 |
| Product Certifications | UL listed |

Packing Units

| • | |
|------------------------------|----------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 13.0 cm |
| Package 1 Width | 5.3 cm |
| Package 1 Length | 4.4 cm |
| Package 1 Weight | 38.0 g |
| Unit Type Of Package 2 | S03 |
| Number Of Units In Package 2 | 80 |
| Package 2 Height | 30.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 3.548 kg |

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| Ø | Reach Free Of Svhc | |
|----------|----------------------------|-----|
| Ø | Toxic Heavy Metal Free | |
| ⊘ | Mercury Free | |
| ⊘ | Rohs Exemption Information | Yes |


Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | End of Life Information |

XB5AA831

Dimensions Drawings

Dimensions



e: clamping thickness: 1 to 6 mm / 0.04 to 0.24 in.


(1) Actuation distance: see table below

| | Actuation distance in mm Actuation distance | | |
|----------|---|---------------|--|
| XB5AA801 | 36 to 145 | 1.42 to 5.71 | |
| XB5AA802 | 145 to 255 | 5.71 to 10.04 | |

Mounting and Clearance

Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for


Connection by Screw Clamp Terminals or Plug-in Connectors or on Printed Circuit Board



- (1) Diameter on finished panel or support
- (2) For selector switches and Emergency stop buttons, use of an anti-rotation plate type ZB5AZ902 is recommended.
- (3) Ø22.5 mm recommended (Ø22.3 $_0^{+0.4}$) / Ø0.89 in. recommended (Ø0.88 in. $_0^{+0.016}$)

| | | | | • |
|---|---------|----------|---------|----------|
| Connections | a in mm | a in in. | b in mm | b in in. |
| By screw clamp terminals or plug-in connector | 40 | 1.57 | 30 | 1.18 |
| By Faston connectors | 45 | 1.77 | 32 | 1.26 |
| On printed circuit board | 30 | 1.18 | 30 | 1.18 |

Detail of Lug Recess



- (1) Diameter on finished panel or support
- (2) For selector switches and Emergency stop buttons, use of an anti-rotation plate type ZB5AZ902 is recommended. (3) \emptyset 22.5 mm recommended (\emptyset 22.3 $_0^{+0.4}$) / \emptyset 0.89 in. recommended (\emptyset 0.88 in. $_0^{+0.016}$)