# XB6AW4B1B PUSHBUTTON 240VAC 1.5AMP XB6 +OPTIONS



Product availability: Stock - Normally stocked in distribution facility

## Main

Plastic
XB6
0.63 in (16 mm)



Complementary

Line Rated Current	5 A	
Electrical connection	Quick connect terminals	
Light block supply	Full voltage 24 V AC	
Operator profile	Flush	
Utilisation category	DC-13 AC-15	

#### Environment

NEMA degree of protection	NEMA 4/4X/12
Product certifications	UL listed file E164353 CCN NKCR CE CSA LR 44087 class 3211 03

### Ordering and shipping details

Category	22459 - PUSHBUTTONS, 16MM
Discount Schedule	CS2
GTIN	00785901356585
Package weight(Lbs)	0.09 kg (0.2 lb(US))
Returnability	Yes
Country of origin	MX

## Offer Sustainability

Green Premium product
WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Declaration
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
€Yes
China RoHS Declaration

Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Contractual warranty	
Warranty	18 months