Product data sheet

Specifications





Illuminated push button, Harmony XB7, green projecting, 22mm, integral LED, push and push to release, 1NO, 24V AC

XB7NJ03B1

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 61.80 USD

Main

| Range Of Product | Harmony XB7 |
|---------------------------------|--|
| Product Or Component Type | Illuminated push-button |
| Device Short Name | XB7 |
| Mounting Diamete | 0.87 in (22 mm) |
| Sale Per Indivisible Quantity | 10 |
| Ip Degree Of Protection | IP20 IEC 60529 rear face) IP65 IEC 60529 front face) |
| Shape Of Signaling Unit Head | Round |
| Type Of Operator | push and push-to-release |
| Operator Profile | Green projecting, unmarked |
| Operator Additional Information | With plain lens |
| Contacts Type And Composition | 1 NO |
| Connections - Terminals | Screw clamp terminals, <= 2 x 1.5 mm² with cable end IEC 60947-1 Screw clamp terminals, 1 x 0.342 x 2.5 mm² without cable end IEC 60947-1 |
| Light Source | LED |
| Bulb Base | Integral LED |
| [Us] Rated Supply Voltage | 24 V AC/DC |
| Device Presentation | Monolithic product |

Complementary

| Cad Overall Width | 1.14 in (29 mm) |
|-------------------------------|--|
| Cad Overall Height | 1.14 in (29 mm) |
| Cad Overall Depth | 2.26 in (57.5 mm) |
| Terminals Description Iso N°1 | (13-14)NO |
| Net Weight | 0.05 lb(US) (0.023 kg) |
| Device Mounting | Fixing hole 0.89 in (22.5 mm) 22.3 +0.4/0 IEC 60947-1 |
| Fixing Center | >= 30 x 40 mm support panel) metal 0.040.24 in (16 mm) >= 30 x 40 mm support panel) plastic 0.080.24 in (26 mm) |
| Fixing Mode | Fixing nut beneath head 17.7021.24 lbf.in (22.4 N.m) |
| Contact Operation | Slow-break |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Positive Opening | With (only NO) |
|---|--|
| Mechanical Durability | 300000 cycles |
| Tightening Torque | 7.0810.62 lbf.in (0.81.2 N.m) IEC 60947-1 |
| Shape Of Screw Head | Cross JIS No 1 |
| | Cross Philips no 1 |
| | Cross pozidriv No 1 |
| | Slotted flat Ø 4 mm |
| | Slotted flat Ø 5.5 mm |
| Short-Circuit Protection | 4 A cartridge fuse gG IEC 60947-5-1 |
| [Ui] Rated Insulation Voltage | 250 V 3)IEC 60947-1 |
| [Uimp] Rated Impulse Withstand Voltage | 4 kV IEC 60947-1 |
| [le] Rated Operational Current | 0.1 A 250 V, DC-13, R300 IEC 60947-5-1 |
| | 0.22 A 125 V, DC-13, R300 IEC 60947-5-1 |
| | 0.3 A 240 V, AC-14, D300 IEC 60947-5-1 |
| | 0.6 A 120 V, AC-14, D300 IEC 60947-5-1 |
| Electrical Durability | 1000000 cycles, DC-13, 0.3 A 24 V 216000 cyc/mn 0.5 IEC 60947-5-1 appendix C |
| | 1000000 cycles, AC-15, 0.03 A 230 V 216000 cyc/mn 0.5 IEC 60947-5-1 appendix C |
| | 1000000 cycles, AC-15, 0.09 A 240 V 108000 cyc/mn 0.5 IEC 60947-5-1 appendix C |
| Electrical Reliability | Λ <= 10exp(-6) 17 V 5 mA IEC 60947-5-4 |
| Signalling Type | Steady |
| Supply Voltage Limits | 19.230 V DC |
| | 21.626.4 V AC |
| Current Consumption | 1827 mA |
| | |

Environment

| Protective Treatment | тн |
|---------------------------------------|--|
| Ambient Air Temperature For Storage | -40158 °F (-4070 °C) |
| Ambient Air Temperature For Operation | -13158 °F (-2570 °C) |
| Electrical Shock Protection Class | Class II IEC 61140 |
| Nema Degree Of Protection | NEMA 12 UL 50 E |
| Standards | IEC 60947-5-1 IEC 60947-1 CSA C22.2 No 14 UL 508 JIS C8201-5-1 JIS C8201-1 |
| Product Certifications | CCC GOST |
| Vibration Resistance | 5 gn 2500 Hz)IEC 60068-2-6 |
| Shock Resistance | 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27 30 gn 18 ms) half sine wave acceleration |
| Electromagnetic Emission | Class B IEC 55011 |

Ordering and shipping details

| Category | US10CS222464 |
|-------------------|---------------|
| Discount Schedule | 0CS2 |
| Gtin | 3606480470356 |
| Returnability | No |

Country Of Origin

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|------------------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 2.36 in (6 cm) |
| Package 1 Width | 1.26 in (3.2 cm) |
| Package 1 Length | 1.26 in (3.2 cm) |
| Package 1 Weight | 0.88 oz (25 g) |

Contractual warranty

Warranty 18 months

Sustainability Screen Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards


| Reach Regulation | REACh Declaration |
|--------------------------|--|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| | |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Weee Circularity Profile | · · · · · · · · · · · · · · · · · · · |

XB7NJ03B1

Dimensions Drawings

Illuminated Pushbutton

Dimensions




e Support panel thickness: 1 to 6 mm/0.4 to 0.24 in. (metal), 2 to 6 mm/0.8 to 0.24 in. (plastic).

XB7NJ03B1

Mounting and Clearance


Mounting

Diameter of Finished Fixing Holes



- (1) Minimum value.
- (2) 40 mm/1.58 in. for Emergency switching off pushbutton only.
- (3) Standard value: Ø 22.3 (0; + 0.4) mm/Ø 0.88 (0; + 0.02) in.

"U" Type Tag Connection



- (1) 6.5 mm/0.26 in. recommended, 7 mm/0.28 in. max.
- (2) M3 screw clamp terminal.

Product data sheet

XB7NJ03B1

Connections and Schema

Wiring Diagram

