

Product data sheet

Specifications



Advanced touchscreen panel with keyboard, Harmony XBTGK, 320 x 240 pixels QVGA, 5.7, standard LCD

XBTGK2120

⚠ Discontinued - Service only

⚠ Discontinued on: Dec 31, 2016

⚠ To be end-of-service on: Dec 31, 2025

Main

Range Of Product	Harmony XBTGK
Product Or Component Type	Advanced touchscreen panel with keyboard
Display Type	Backlit monochrome STN LCD
Display Colour	Black and white 16 levels of grey
Display Resolution	320 x 240 pixels QVGA
Display Size	5.7 inch
Software Type	Configuration software
Software Designation	Vijeo Designer
Operating System	Harmony
Processor Name	CPU RISC
Processor Frequency	133 MHz
Memory Description	512 KB SRAM back up of data lithium battery 16 MB flash EPROM application memory
Integrated Connection Type	RJ45 COM2 serial link RS485 <= 187.5 kbit/s Siemens MPI (187.5 kbits/s) 1 USB type A master port (V1.1) Modicon M340 terminal port communication male SUB-D 9 COM1 serial link RS232C/RS422/RS485 <= 115.2 kbits/s removable screw terminal block power supply
Resistance To Electrostatic Discharge	4 kV IEC 61000-4-2 level 3
Cut-Out Dimensions	209 (+/- 0.4) x 243 (+/- 0.4) mm

Complementary

Touch Sensitive Zone	1024 x 1024
Touch Panel	Analogue
Backlight Lifespan	58000 hours
Brightness	8 levels via touch panel
Contrast	8 levels via touch panel
Character Font	Chinese (simplified Chinese) Japanese (ANK, Kanji) Korean ASCII (European characters) Taiwanese (traditional Chinese)
[Us] Rated Supply Voltage	24 V DC

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Supply	External source
Supply Voltage Limits	19.2...28.8 V
Inrush Current	30 A
Power Consumption In W	26 W
Number Of Dynamic Function Keys Symb	14 with LED
Number Of Static Function Keys	10 with LED and labels
Number Of Service Keys	8
Number Of Alphanumeric Keys	12
Local Signalling	for normal operation or backlighting faulty 1 LED (green or orange)
Number Of Pages	Limited by internal memory capacity
Downloadable Protocols	Telemecanique Modicon FIPWAY Telemecanique Modicon Modbus Plus Telemecanique Modicon Modbus TCP Telemecanique Modicon Modbus Mitsubishi Melsec third party protocols Omron Sysmac third party protocols Rockwell Automation Allen-Bradley third party protocols Siemens Simatic third party protocols Telemecanique Modicon Uni-TE
Realtime Clock	Built-in
Data Storage Equipment	1 Compact Flash card >= 1 GB
Use Of Slot	For 1 fieldbus communication card (Device Net, Profibus DP)
Port Ethernet	10BASE-T/100BASE-TX
Product Mounting	Flush mounting
Fixing Mode	By 10 spring clips By 4 screw clamps
Front Material	Aluminium alloy
Enclosure Material	PPT
Marking	CE
Width	8.67 in (220.3 mm)
Height	10.43 in (265 mm)
Depth	2.37 in (60.3 mm)

Environment

Immunity To Microbreaks	5 ms
Standards	UL 508 FCC Class A IEC 61000-6-2 UL 1604 EN 61131-2 CSA C22.2 No 14
Product Certifications	cULus C-tick CSA Class 1 Division 2 T5 UL Class 1 Division 2 T4A UL Class 1 Division 2 T5 CSA Class 1 Division 2 T4A
Ambient Air Temperature For Operation	32...122 °F (0...50 °C)
Ambient Air Temperature For Storage	-4...140 °F (-20...60 °C)
Relative Humidity	0...90 % without condensation

Operating Altitude	< 6561.68 ft (2000 m)
Ip Degree Of Protection	IP20 IEC 60529 rear panel) IP65 IEC 60529 front panel)
Nema Degree Of Protection	NEMA 4X front panel (indoor use)
Shock Resistance	15 gn 11 ms IEC 60068-2-27
Vibration Resistance	1 gn 9...150 Hz)IEC 60068-2-6 3.5 mm 5...9 Hz)IEC 60068-2-6
Resistance To Electromagnetic Fields	9.14 V/m (10 V/m) IEC 61000-4-3
Resistance To Fast Transients	2 kV IEC 61000-4-4 level 3

Ordering and shipping details

Category	22569-MAGELIS XBT-GT (AND XBT-G)
Discount Schedule	MC2
Gtin	3595863961812
Returnability	No
Country Of Origin	CN

Packing Units


Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.27 in (21.0 cm)
Package 1 Width	14.57 in (37.0 cm)
Package 1 Length	15.35 in (39.0 cm)
Package 1 Weight	7.48 lb(US) (3.392 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Dimensions Drawings

Dimensions




Product Reference	a	b	c
XBTGK2120 XBTGK2330	265 mm/10.43 in.	60.3 mm/2.37 in.	220.3 mm/8.67 in.
XBTGK5330	332 mm/13.07 in.	72.7 mm/2.86 in.	296 mm/11.65 in.

Mounting and Clearance


Clearance

Installation Requirements

For easier maintenance, operation and improved ventilation, be sure to install the unit at least 100 mm (3.94 in) away from adjacent structures and other equipment:



Panel Cut-out Dimensions



Dimensions in mm

Graphic Display Terminal	Cut-out for Flush Mounting			
	H	G	r	Panel Thickness
XBTGK2120 XBTGK2330	243 (-/+ 0.4)	209 (-/+ 0.4)	3 max.	1.6 ... 10
XBTGK5330	309 (-/+ 0.4)	285 (-/+ 0.4)	3 max.	1.6 ... 10

Dimensions in in.

Graphic Display Terminal	Cut-out for Flush Mounting			
	H	G	r	Panel Thickness
XBTGK2120 XBTGK2330	9.57 (-/+ 0.02)	8.23 (-/+ 0.02)	0.12 max.	0.06 ... 0.39
XBTGK5330	12.17 (-/+ 0.02)	11.22 (-/+ 0.02)	0.12 max.	0.06 ... 0.39