# **Product datasheet**

Specifications





# module XPSAT - Emergency stop - 230 V AC

XPSATE3710P

- ! Discontinued on: 31-Dec-2023
- ! End-of-service on: 31-Dec-2023

① Discontinued - Service only

# Main

Range Of Product	Preventa Safety automation
Product Or Component Type	Preventa safety module
Safety Module Name	XPSATE
Safety Module Application	For emergency stop and switch monitoring
Function Of Module	Emergency stop button with 2 NC contacts
Safety Level	Can reach PL d/category 3 time delay safety outputs conforming to EN/ISO 13849-1 Can reach PL e/category 4 instantaneous safety outputs conforming to EN/ISO 13849-1 Can reach SILCL 3 instantaneous safety outputs conforming to EN/IEC 62061 Can reach SILCL 2 time delay safety outputs conforming to EN/IEC 62061
Safety Reliability Data	DC > 99 % conforming to EN/ISO 13849-1 instantaneous safety outputs MTTFd = 134.8 years conforming to EN/ISO 13849-1 instantaneous safety outputs MTTFd = 54.5 years conforming to EN/ISO 13849-1 time delay safety outputs DC > 98.4 conforming to EN/ISO 13849-1 time delay safety outputs PFHd = 6.81E-9 1/h conforming to EN/IEC 62061 instantaneous safety outputs PFHd = 1.96E-8 1/h conforming to EN/IEC 62061 time delay safety outputs
Type Of Start	Configurable
Connections - Terminals	Captive screw clamp terminals, removable terminal block, 1 x 0.21 x 2.5 mm² flexible with cable end, with double bezel Captive screw clamp terminals, removable terminal block, 1 x 0.21 x 2.5 mm² solid with cable end, with double bezel Captive screw clamp terminals, removable terminal block, 1 x 0.251 x 2.5 mm² flexible with cable end, with double bezel Captive screw clamp terminals, removable terminal block, 2 x 0.22 x 1 mm² solid with cable end, with double bezel Captive screw clamp terminals, removable terminal block, 2 x 0.22 x 1.5 mm² flexible with cable end, with double bezel Captive screw clamp terminals, removable terminal block, 2 x 0.252 x 1 mm² flexible with cable end, with double bezel Captive screw clamp terminals, removable terminal block, 2 x 0.52 x 1.5 mm² flexible with cable end, with double bezel
Output Type	Relay instantaneous opening, 2 NO circuit(s), volt-free Relay time delay opening, 3 NO circuit(s), volt-free
Number Of Additional Circuits	3 solid state outputs
[Us] Rated Supply Voltage	230 V AC - 2010 %

# Complementary

Synchronisation Time Between Inputs	75 ms
Supply Frequency	50/60 Hz
Maximum Power Consumption In W	8 W
Input Protection Type	Internal, electronic

21-Jun-2024 Life Is On Schneider

Time Delay Range	030 s
[Uc] Control Circuit Voltage	48 V DC
Breaking Capacity	180 VA holding AC-15 C300 relay output
	1800 VA inrush AC-15 C300 relay output
Breaking Capacity	1 A at 24 V (DC-13) time constant: 50 ms for relay output
Output Thermal Current	2.5 A for time delay outputs
	5 A for instantaneous outputs
[Ith] Conventional Free Air Thermal Current	8 A
Associated Fuse Rating	4 A gG for time delay outputs conforming to EN/IEC 60947-5-1, DIN VDE 0660 part 200
	6 A gG for instantaneous outputs conforming to EN/IEC 60947-5-1, DIN VDE 0660 part 200
Minimum Output Current	10 mA for relay output
Minimum Output Voltage	17 V for relay output
Maximum Response Time On nput Open	20 ms
Ui] Rated Insulation Voltage	300 V (pollution degree 2) conforming to IEC 60947-5-1 300 V (pollution degree 2) conforming to DIN VDE 0110 part 1
Uimp] Rated Impulse Withstand Voltage	4 kV overvoltage category III conforming to IEC 60947-5-1 4 kV overvoltage category III conforming to DIN VDE 0110 part 1
Local Signalling	4 LEDs
Mounting Support	35 mm symmetrical DIN rail
Net Weight	0.38 kg
Environment	
Standards	EN/IEC 60204-1
	EN/ISO 13850 EN/IEC 60947-5-1
Product Certifications	CSA
	UL TÜV
p Degree Of Protection	IP20 (terminals) conforming to EN/IEC 60529
	IP40 (enclosure) conforming to EN/IEC 60529
Ambient Air Temperature For Operation	-1055 °C

Standards	EN/IEC 60204-1 EN/ISO 13850	
	EN/IEC 60947-5-1	
Product Certifications	CSA	
	UL	
	ΤÜV	
Ip Degree Of Protection	IP20 (terminals) conforming to EN/IEC 60529	
	IP40 (enclosure) conforming to EN/IEC 60529	
Ambient Air Temperature For Operation	-1055 °C	
Ambient Air Temperature For Storage	-2585 °C	

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	12.5 cm
Package 1 Width	6.2 cm
Package 1 Length	10.5 cm
Package 1 Weight	510.0 g

# **Contractual warranty**

Warranty 18 months



**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

# Well-being performance

<b>Ø</b>	Mercury Free	
	Rohs Exemption Information	Yes
<b>②</b>	Pvc Free	

### **Certifications & Standards**

Circularity Profile	End of Life Information
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
<b>Environmental Disclosure</b>	Product Environmental Profile
China Rohs Regulation	China RoHS declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Reach Regulation	REACh Declaration

# XPSATE3710P

### **Dimensions Drawings**

### **Dimensions**

