



PRODUCT-DETAILS

XT1H 125 TMF 100-1000 3p F F UL/CSA

XT1H 125 TMF 100-1000 3p F F UL/CSA



General Information	
Extended Product Type	XT1H 125 TMF 100-1000 3p F F UL/CSA
Product ID	1SDA074706R1
EAN	8015644786830
Catalog Description	XT1H 125 TMF 100-1000 3p F F UL/CSA
Long Description	C.BREAKER TMAX XT1H 125 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMF R 100-1000 A

ABB EcoSolutions	
ABB EcoSolutions	Yes
ABB Site Meeting Group Waste To Landfill Target	UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions	9AKK108468A2347
Environmental Product Declaration - EPD	9AKK108468A1890
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 55.9 %

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	5b7a7380-c053-433a-9f61-08fa87722d7b Italy (IT)
Simplified SCIP	e0586616-1069-4194-b884-80e044d27193 Germany (DE) 37c6df43-5e1b-4817-b794-339ac18e23a6 Croatia (HR) 37f6e4cc-48cd-4fea-a24f-03cac81d35c3 Czech Republic (CZ) fc0cee72-60eb-4d8e-8a8d-eaeb44aab19 Denmark (DK) 17367a5e-3f4d-49e3-b5e5-9c543ad6bf94 Sweden (SE) eb2f426b-7b73-4cea-881a-d7dd0ad79c2d Germany (DE) c23ff3ce-9400-4e4e-927b-ad22450fb521 France (FR) ebeae46e-76b7-4513-92e4-f800040c451e Germany (DE) 9261ffca-86bc-405b-91f4-319fd846ddc6 Hungary (HU) 1fa6f5fc-7ba3-4dda-a01d-f6adab7893b2 Spain (ES) 075b1678-7e71-48cd-9824-fc260f2f152e Belgium (BE) 3bd5d061-e310-4064-b60c-6b3bd7f94885 France (FR) b980ed83-55d9-4544-990c-daa669a4b982 Poland (PL) 2562a00b-094b-4ff0-8520-de14820294fd Germany (DE) 78898227-54dd-4a64-bcd4-e3fc834099f2 Germany (DE) 064d5381-d941-4413-aca7-e7b73cd64aeb Portugal (PT) 949f3ba9-8f37-4702-a1f6-180ea8467b98 Poland (PL) 2e4d5011-a2c7-4793-9bea-a292444c8bb4 Netherlands (NL) f6087d44-cd7a-47ec-94a7-5737a8cb8e60 Sweden (SE) 0f434782-16d3-4e4a-b24b-e9cb81c9f4da Norway (NO) 6fe277ca-3bf6-4ed1-90d7-8bbfd05cf69a Bulgaria (BG) b7c3cec4-ee79-4e84-8c3e-26c94501e45e Poland (PL) d2503023-b537-4a63-84f4-50a3fed6dbdb Finland (FI) 42d1e26f-e329-4a45-8fd9-3cc95ce7a224 Hungary (HU) c8c834db-a5d2-4cbe-89a1-9b6710822da8 Greece (GR) 256ff5cf-d3b5-4e0b-9f9f-88f7afc88917 Estonia (EE) 26b02900-a58a-45ed-a2ee-0b51d4aac893 Belgium (BE)

Environmental

Environmental Information	9AKK108467A6707
---------------------------	-----------------

Ordering

Order Code US and Canada	XT1HU3100AFF000XXX
EAN	8015644786830
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	76.2 mm
Product Net Height	130 mm
Product Net Depth / Length	70 mm
Product Net Weight	1.1 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	128 mm
Package Level 1 Height	135 mm
Package Level 1 Depth / Length	143 mm
Package Level 1 Gross Weight	1.1 kg
Package Level 1 EAN	8015644786830

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Suitable for Product Class	SACE Tmax XT
Version	F
CAD Dimensional Drawing	1SDH001295R0008

Technical

Connecting Capacity Main Circuit	Busbar 45.5 ... 80 mm ²
Current Type	AC/DC
Electrical Durability	120 cycles per hour 8000 cycle
Mechanical Durability	240 cycles per hour 25000 cycle
Number of Poles	3P
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 7 W
Rated Current (I_n)	100 A
Rated Instantaneous Short-Circuit Current Setting (I_i)	1000 A
Rated Operational Voltage	600Y/347 V AC 500 V DC
Rated Uninterrupted Current (I_u)	125 A
Rated Voltage (U_r)	600Y/347 V
Recommended Screw Driver	Main Circuit M6
Release	TMF
Release Type	TM
Setting Range	100 A
Short-Circuit Performance Level	H
Standards	UL489
Sub-type	XT1

Terminal Connection Type	Front
Terminal Type	Bolt
Tightening Torque	6 N·m

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 100 kA (480 V AC) 65 kA (600Y / 347 V AC) 25 kA (250 V DC) 2 Poles in Series 50 kA (500 V DC) 4 Poles in Series Kind 50 kA
-----------------------------------	---

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	9AKK10103A3905
Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK106713A5532
UL Certificate	1SDL000163R0111
VDE Certificate	No certification needed
Dimension Diagram	1SDH000719R0100
Mechanical Drawings	1SDH000719R0100
Wiring Diagram	1SDM000068R0001
Instructions and Manuals	1SDH000719R0003

External Classifications and Standards

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4927 >> Molded case circuit breakers
Object Classification Code	Q
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Where Used (as part of "kit")

Identifier	Description	Type
3HAC058322-001	Circuit breaker UL, w term.	Kit

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

Robotics → Controllers → IRC5 → IRC5 Process Module

