



PRODUCT-DETAILS

XT1N 125 TMF 15-500 3p F F UL/CSA
XT1N 125 TMF 15-500 3p F F UL/CSA



General Information	
Extended Product Type	XT1N 125 TMF 15-500 3p F F UL/CSA
Product ID	1SDA074634R1
EAN	8015644785017
Catalog Description	XT1N 125 TMF 15-500 3p F F UL/CSA
Long Description	C.BREAKER TMAX XT1N 125 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMF R 15-500 A

ABB EcoSolutions	
ABB EcoSolutions	Yes
ABB Site Meeting Group Waste To Landfill Target	UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions	9AKK108468A2347
Environmental Product Declaration - EPD	9AKK108468A1890
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 55.9 %

Material Compliance	
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	3b8fd9bd-deaf-473e-bca3-5c0c0b9666c2 Italy (IT)
Simplified SCIP	28799f78-41f1-43ef-9750-dce0e35fdb5b Germany (DE)
	17a83770-f822-46a0-802b-dc23c5fc2702 Poland (PL)
	f4346f45-52c4-49e5-a8d8-54538abdf21d Sweden (SE)
	84fdcc71-2463-4498-a627-5ca3d638ce43 Germany (DE)
	ec7ac1dc-189a-4aad-a941-153772199706 Germany (DE)
	a7073941-102f-4509-97f9-467e041f8055 France (FR)
	edb9ce8c-6f42-411d-b9f9-fae52dad0622 Netherlands (NL)
	42d14025-2b5b-4e1b-bce9-2e4932790e5e Spain (ES)
	1f93601f-134c-4ef2-96d4-de0db226527f Netherlands (NL)
	cebfbec4-91a3-4bf1-b691-a80c027b1bcf Greece (GR)
	e09f120e-9e15-4638-b6a2-c0a2e507f345 Czech Republic (CZ)
	2776571a-8624-4643-880f-3e9797cefcae Poland (PL)
	a89e32b3-4dcf-4644-b29a-942861463b95 Portugal (PT)
	a6e9759f-6c08-4bf7-bc09-6cf32cd11308 Bulgaria (BG)
	209b77b7-7ac1-4ec5-a64c-6f27cfc98469 Sweden (SE)
	c8fdb2ae-42fb-4c38-8e1d-c90275d89238 Poland (PL)
	08f59948-b88d-445d-bae1-d6f39f054b01 France (FR)
	6bc169d8-6733-42bd-a5be-82672f29e01b Netherlands (NL)
	804b311e-c4d0-417e-a70e-0b29ffdc9e4c Netherlands (NL)
	f819a920-c1ba-441e-94df-037de80cfa36 Estonia (EE)
	8bc5b015-24e4-446b-837f-7355a98891d5 Germany (DE)
	4a65bf7b-ceec-40e3-bfd9-5d0b7c839f4c Denmark (DK)
	3c8c532a-4aa7-4077-a2ec-c5472133443c Germany (DE)
	a376e9fa-2c7a-4d8c-8895-3e0fb76e7ece Croatia (HR)
	19082ec1-7c96-4c17-a48f-ea35c831683c Norway (NO)
	5514ef58-59a4-4242-8385-c98eaa8300f3 Finland (FI)
	3b5652aa-e465-4976-99c5-5d2cf9e4a0d5 Netherlands (NL)

Environmental	
Environmental Information	9AKK108467A6707

Ordering	
Order Code US and Canada	XT1NU3015AFF000XXX
EAN	8015644785017
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	76.2 mm
Product Net Height	130 mm
Product Net Depth / Length	70 mm
Product Net Weight	1.1 kg

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	128 mm
Package Level 1 Height	135 mm
Package Level 1 Depth / Length	143 mm
Package Level 1 Gross Weight	1.1 kg
Package Level 1 EAN	8015644785017

Additional Information	
Circuit Breaker Type to be Associated	Power Distribution
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Suitable for Product Class	SACE Tmax XT
Version	F
CAD Dimensional Drawing	1SDH001295R0008

Technical	
Connecting Capacity Main Circuit	Busbar 45.5 ... 80 mm ²
Current Type	AC/DC
Electrical Durability	120 cycles per hour 8000 cycle
Mechanical Durability	240 cycles per hour 25000 cycle
Number of Poles	3P
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 1.1 W
Rated Current (I _n)	15 A
Rated Instantaneous Short-Circuit Current Setting (I _i)	500 A
Rated Operational Voltage	600Y/347 V AC 500 V DC
Rated Uninterrupted Current (I _u)	125 A
Rated Voltage (U _r)	600Y/347 V
Recommended Screw Driver	Main Circuit M6
Release	TMF
Release Type	TM
Setting Range	15 A
Short-Circuit Performance Level	N
Standards	UL489
Sub-type	XT1

Terminal Connection Type	Front
Terminal Type	Bolt
Tightening Torque	6 N·m

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 50 kA (480 V AC) 25 kA (600Y / 347 V AC) 18 kA (250 V DC) 2 Poles in Series 35 kA (500 V DC) 4 Poles in Series Kind 35 kA
-----------------------------------	--

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	9AKK10103A3905
Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK106713A5532
UL Certificate	1SDL000163R0111
VDE Certificate	No certification needed
Dimension Diagram	1SDH000719R0100
Mechanical Drawings	1SDH000719R0100
Wiring Diagram	1SDM000068R0001
Instructions and Manuals	1SDH000719R0003

External Classifications and Standards

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4927 >> Molded case circuit breakers
Object Classification Code	Q
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

