



**Catalog Number:** XT1NU3125AAF000XXX  
**UPC Number:** 88861448948  
**Status:** Active

Tmax XT Molded Circuit Breaker, Frame Size XT1 - to 125A, 600Y/347V (UL) / 160A, 690V (IEC), Trip Type Thermal magnetic fixed (TMF), 3 Poles

#### North American Specifications (UNSPSC)

|                  |                                                                                                                                                                       |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| UNSPSC           | 39121616 Molded case circuit breakers                                                                                                                                 |
| IGCC             | 4927 Molded case circuit breakers                                                                                                                                     |
| Brand Name       | ABB                                                                                                                                                                   |
| Sub Brand        | Tmax XT                                                                                                                                                               |
| Type             | Molded case circuit breaker                                                                                                                                           |
| Special Features | Feature high specific let-through current peak and energy limiting characteristics that allow the circuits and equipment on the load side to be sized in Optimum way. |
| Application      | Ideal solution for all distribution levels from the main low voltage switchboard to the subswitchboards in the installation                                           |
| Standard         | UL 80% rated / IEC dual rated                                                                                                                                         |
| Frame            | XT1 - to 125A, 600Y/347V (UL) / 160A, 690V (IEC)<br>- Thermal magnetic protection                                                                                     |
| Trip Type        | Thermal magnetic fixed (TMF)                                                                                                                                          |
| Number Of Poles  | 3 Poles                                                                                                                                                               |

#### Packaging

|                           |                  |
|---------------------------|------------------|
| Outer Quantity            | 1                |
| Outer Dimensions (inches) | 5.63x5.039x5.315 |
| Weight Uom                | 2.61 lbs. Each   |