



PRODUCT-DETAILS

XT2H 125 TMA 100-500..1000 3p F F UL/CSA

XT2H 125 TMA 100-500..1000 3p F F UL/CSA



General Information	
Extended Product Type	XT2H 125 TMA 100-500..1000 3p F F UL/CSA
Product ID	1SDA074800R1
EAN	8015644787776
Catalog Description	XT2H 125 TMA 100-500..1000 3p F F UL/CSA
Long Description	C.BREAKER TMAX XT2H 125 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMA R 100 I3=500...1000 A

ABB EcoSolutions	
ABB EcoSolutions	Yes
ABB Site Meeting Group Waste To Landfill Target	UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions	9AKK108468A2348
Environmental Product Declaration - EPD	9AKK108468A1891
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 55.70 %

Material Compliance	
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	ce02b563-7ee3-4d12-b264-102964f5b85d Italy (IT)
Simplified SCIP	8dccbd82-82a1-4560-86a2-c6b0cf8ca067 Belgium (BE) 8f961ddc-1f26-4946-94e6-deef48164072 Spain (ES) 3e2e4335-225e-451b-ba70-6be2f0501599 Hungary (HU) f1a49369-8457-408e-bf54-34320d6e746a Sweden (SE) cf9a2a94-1369-4c47-ba79-035658acdd41 Germany (DE) aae14b91-4bd2-4f0d-ae0f-28cf4034424a Denmark (DK) 07d92320-7670-46be-bcd5-d2a204747d4d Germany (DE) 126533f7-c99b-4af7-91ff-395efdb06b70 Croatia (HR) 82219d04-27bc-4ac3-aa61-f58c269283e4 France (FR) 794c996d-7c8d-4ddd-a112-72578eb67cec Czech Republic (CZ) f7083f06-f9c7-46c2-a9ed-beaa8b2aa099 Portugal (PT) 4f2bf161-4ee8-4361-a9a5-c5ffc8f34fed Netherlands (NL) bfe8da3d-8089-4fac-a342-c0c2836cf8a7 Sweden (SE) d68105ee-6e3b-442e-af82-3f94f9425d56 Norway (NO) 9430212f-5a6d-4b23-a056-99f2d6f27e29 Bulgaria (BG) cffb199f-c0b6-44c9-8a05-48a93cd7aa9a Poland (PL) aa2bb74f-402c-4b51-95d2-9599b0c2debc Germany (DE) 47916e93-80b9-41dc-9ba3-189fddd7cd15 Germany (DE) 1cf3c7fb-b232-499f-b1ff-254be703bddb3 Poland (PL) e37a81b2-c685-49a5-b097-f001217f56a5 Estonia (EE) 3444fda8-482c-482e-a0ba-80c6032b5ecd Belgium (BE) 059fee7d-f17a-4a2b-ae48-b759ab6a4c7a Greece (GR) a2aa15e6-05c0-4831-bd2c-1db811c98570 France (FR) c4f9f022-4f04-4185-815b-d69fb2cf43bb Germany (DE) 9c8bb83b-429d-4a5f-ae78-d00182f65c42 Poland (PL) d6818202-896a-434f-81b1-1d3855c6a9ac Hungary (HU) c935ad34-7018-4b91-bfb6-1c61ebdf1b79 Finland (FI)

Environmental	
Environmental Information	9AKK108467A6707

Ordering	
Order Code US and Canada	XT2HU3100BFF000XXX
EAN	8015644787776
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	90 mm
Product Net Height	130 mm
Product Net Depth / Length	82.5 mm
Product Net Weight	1.1 kg

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	131 mm
Package Level 1 Height	212 mm
Package Level 1 Depth / Length	147 mm
Package Level 1 Gross Weight	1.2 kg
Package Level 1 EAN	8015644787776

Additional Information	
Circuit Breaker Type to be Associated	Power Distribution
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Suitable for Product Class	SACE Tmax XT
Version	F
CAD Dimensional Drawing	1SDH002230A1001

Technical	
Connecting Capacity Main Circuit	Busbar 32.5..100 mm ²
Current Type	AC/DC
Electrical Durability	120 cycles per hour 8000 cycle
Mechanical Durability	240 cycles per hour 25000 cycle
Number of Poles	3P
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 8.1 W
Rated Current (I _n)	100 A
Rated Instantaneous Short-Circuit Current Setting (I _i)	500...1000 A
Rated Operational Voltage	600 V AC 500 V DC
Rated Uninterrupted Current (I _u)	125 A
Rated Voltage (U _r)	600 V
Recommended Screw Driver	Main Circuit M6
Release	TMA
Release Type	TM
Setting Range	70...100 A
Short-Circuit Performance Level	H
Standards	UL489
Sub-type	XT2

Terminal Connection Type	Front
Terminal Type	Bolt
Tightening Torque	6 N·m

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 150 kA (480 V AC) 65 kA (600 V AC) 25 kA (250 V DC) 2 Poles in Series 65 kA (500 V DC) 3 Poles in Series 65 kA
-----------------------------------	---

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	9AKK10103A3906
Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK106713A5901
UL Certificate	1SDL000163R0112
VDE Certificate	No certification needed
Dimension Diagram	1SDH000721R0100
Mechanical Drawings	1SDH000721R0100
Wiring Diagram	1SDM000068R0001
Instructions and Manuals	1SDH000721R0003 1SDH000721R0505

External Classifications and Standards

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4927 >> Molded case circuit breakers
Object Classification Code	Q
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

