



PRODUCT-DETAILS

XT4V 250 Ekip Dip LS/I In=250A 3p F F
UL/CSA

XT4V 250 Ekip Dip LS/I In=250A 3p F F
UL/CSA



General Information	
Extended Product Type	XT4V 250 Ekip Dip LS/I In=250A 3p F F UL/CSA
Product ID	1SDA075411R1
EAN	8015644793883
Catalog Description	XT4V 250 Ekip Dip LS/I In=250A 3p F F UL/CSA
Long Description	C.BREAKER TMAX XT4V 250 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP DIP LS/I R 250 A

ABB EcoSolutions	
ABB EcoSolutions	Yes
ABB Site Meeting Group Waste To Landfill Target	UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions	9AKK108468A2352
Environmental Product Declaration - EPD	9AKK108468A1898
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 56.30 %

Material Compliance		
REACH Declaration		9AKK108466A1425
RoHS Information		9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019	
Conflict Minerals Reporting Template (CMRT)		9AKK108467A5658
Toxic Substances Control Act - TSCA		9AKK108467A8326

Environmental		
Environmental Information		9AKK108467A6707

Ordering		
Order Code US and Canada		XT4VU3250EFF000XXX
EAN		8015644793883
Minimum Order Quantity		1 piece
Customs Tariff Number		85362090

Dimensions		
Product Net Width		105 mm
Product Net Height		160 mm
Product Net Depth / Length		82.5 mm
Product Net Weight		2.5 kg

Container Information		
Package Level 1 Units		box 1 piece
Package Level 1 Width		145 mm
Package Level 1 Height		210 mm
Package Level 1 Depth / Length		168 mm
Package Level 1 Gross Weight		2.5 kg
Package Level 1 EAN		8015644793883

Additional Information		
Circuit Breaker Type to be Associated		Power Distribution
Product Main Type		SACE Tmax XT
Product Name		Moulded Case Circuit Breaker
Product Type		Automatic Circuit Breaker
Suitable for Product Class		SACE Tmax XT
Version		F

Technical

Connecting Capacity Main Circuit	Busbar 85..200 mm ²
Current Type	AC
Electrical Durability	120 cycles per hour 8000 cycle
Mechanical Durability	240 cycles per hour 25000 cycle
Number of Poles	3P
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 16.4 W
Rated Current (I _N)	250 A
Rated Operational Voltage	600 V AC
Rated Uninterrupted Current (I _u)	250 A
Rated Voltage (U _r)	600 V
Recommended Screw Driver	Main Circuit M8
Release	Ekip Dip LS/I
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL489
Sub-type	XT4
Terminal Connection Type	Front
Terminal Type	Bolt
Tightening Torque	8 N·m

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 200 kA (480 V AC) 150 kA (600 V AC) 65 kA
--------------------------------------	--

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	9AKK10103A3908
Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK106713A5529
UL Certificate	1SDL000163R0114
VDE Certificate	No certification needed
Dimension Diagram	1SDH000722R0100
Mechanical Drawings	1SDH000722R0100
Wiring Diagram	1SDM000068R0001

External Classifications and Standards

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4932 >> 3 Pole Non-Interchangeable Trip Electronic Circuit Breakers
Object Classification Code	Q
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

