Product datasheet

Specifications





AS-Interface, Base unit with cover, Harmony XVB Universal, side cable entry, plastic, black, 70mm, AS-Interface connection

XVBC21A

Main

Range of product	Harmony XVB Universal
Product or component type	Base unit with cover
Component name	XVRC

Complementary

Range compatibility	AS-Interface cabling system	
Material	Glass reinforced polyamide: base unit Polycarbonate: cover unit	
Mounting diameter	70 mm	
[Us] rated supply voltage	External: 19.230 V AS-Interface line: 2431.6 V	
Current consumption	250 mA under load via AS-Interface line 30 mA under load external 30 mA no load	
Actuator sensor interface profile [AS-i]	S.7.F	
Electrical connection	1 connector M12 for AS-Interface line	
Cable entry	Side entry	
Assembly style	Customer assembly, up to 5 units	
[Ui] rated insulation voltage	250 V conforming to IEC 60947-1	
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60947-1	
Terminals description ISO n°1	(COM-5)PW (COM-1)PW (COM-4)PW (COM-3)PW (GND)GROUND (COM-2)PW	
Net weight	0.19 kg	

Environment

Product certifications	AS-Interface No 25701 CSA
Standards	EN/IEC 60947-5-1
protective treatment	TC
ambient air temperature for storage	-2070 °C
Ambient air temperature for operation	-1050 °C
Shock resistance	25 gn conforming to IEC 60068-2-27

Vibration resistance	5 gn conforming to IEC 60068-2-6
Overvoltage category	Class I conforming to IEC 60536
IP degree of protection	IP65 conforming to IEC 60529
NEMA degree of protection	NEMA 4X conforming to UL 508 (indoor)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.2 cm
Package 1 Width	7.8 cm
Package 1 Length	7.8 cm
Package 1 Weight	238.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	36
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	9.079 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations


XVBC21A

Dimensions Drawings

Indicator Bank without "Flash" Discharge Tube Unit

Dimensions

Below drawing shows the minimum configuration of the product. Select the number of stages according to the product characteristics in order to get \mathbf{b} dimension.



- (1) Base unit
- (2) Illuminated or audible signalling unit XVBC•••, to be ordered separately
- (3) Cover (supplied with base unit)

Number of illuminated or audible signalling units (no "flash")		b in in.
1	138	5.43
2	201	7.91
3	264	10.39
4	327	12.87


Product datasheet

XVBC21A

Mounting and Clearance

Base Unit for Indicator Banks

Panel Cut-out for Direct Fixing



Product datasheet

XVBC21A

Connections and Schema

Illuminated Beacon

Wiring Diagram

