

Complete beacon, Harmony XVB Universal, indicating 230 VAC 10

XVBL4M3

! Discontinued on: 1 Nov 2020

① Discontinued

Main

| Range of product | Harmony XVB Universal |
|------------------------------------|--|
| Product or component type | Complete beacon |
| Beacon or indicator bank unit type | Base unit direct or tube fixing Illuminated unit |
| Signalling type | Flashing |
| Mounting diameter | 70 mm |
| Component name | XVBL |
| Material | Glass reinforced polyamide: base unit Polycarbonate: illuminated unit |
| Light source | Bulb not included, green |
| Bulb type | Incandescent with BA 15d base Protected LED |
| [Us] rated supply voltage | 48230 V AC |
| Maximum power dissipation in W | 7 W |

Complementary

| Connections - terminals | Screw clamp terminals, <= 1 x 1.5 mm² with cable end |
|--|--|
| [Ui] rated insulation voltage | 250 V conforming to IEC 60947-1 |
| Nominal voltage limit | 0.851.1 Un conforming to IEC 60947-5-1 |
| [Uimp] rated impulse withstand voltage | 4 kV conforming to IEC 60947-1 |
| Flashing frequency | 1 Hz |
| CAD overall width | 70 mm |
| CAD overall height | 139 mm |
| CAD overall depth | 70 mm |
| Terminals description ISO n°1 | (GND)GROUND (COM-1)PW |
| Net weight | 0.28 kg |

Environment

| Pollution degree | 2 |
|------------------------|-----------------|
| Product certifications | CCC |
| | EAC |
| | CSA C22-2 No 14 |
| | UL 508 |

| Standards | EN/IEC 60947-5-1 |
|-------------------------------------|--|
| protective treatment | TC |
| Ambient air temperature for storage | -4070 °C |
| Electrical shock protection class | Class I on support tube conforming to IEC 61140 Class II on base unit conforming to IEC 61140 |
| IP degree of protection | IP65 on fixing base XVBZ0. conforming to IEC 60529 IP66 on base unit conforming to IEC 60529 |
| NEMA degree of protection | Type 4X conforming to UL (indoor) |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|---------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 14.5 cm |
| Package 1 Width | 8 cm |
| Package 1 Length | 8 cm |
| Package 1 Weight | 280 g |

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards


| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
|--------------------------|---|
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | No need of specific recycling operations |

XVBL4M3

Dimensions Drawings

Illuminated Beacon for BA 15d Bulb or LED

Dimensions



Product datasheet

XVBL4M3

Connections and Schema

Illuminated Beacon

Wiring Diagram

