## **Product data sheet**

Specification





# Pilot light, Harmony XVL, plastic, green, 12mm, covered LED, 24V DC

XVLA333

Product availability: Stock - Normally stocked in distribution facility

Price\*: 52.00 USD

#### Main

Range Of Product	Harmony XVL			
Product Or Component Type	LED pilot light with integral lens cap			
Component Name	XVL			
Mounting Diameter	0.47 in (12 mm)			
Light Source	Covered LED			
Light Block Colour	Green			
Protection Type	Integral ballast resistor Built-in by diode			
[Us] Rated Supply Voltage	24 V			
Ip Degree Of Protection	IP65 IEC 60529 with seal XVLZ912) IP65 NF C 20-010 with seal XVLZ912) IP40 IEC 60529 IP40 NF C 20-010			

#### Complementary

Supply Circuit Type	DC			
Connections - Terminals	Threaded connector 1 x 0.21 x 1.5 mm <sup>2</sup>			
Current Consumption	18 mA			
[Ui] Rated Insulation Voltage	50 V IEC 60947-1			
Bulb Lifespan	100000 h			
Nominal Voltage Limit	0.81.1 Un			
Terminals Description Iso N°1	(X1-X2)PL			
Height	0.63 in (16 mm)			
Width	0.63 in (16 mm)			
Depth	2.01 in (51 mm)			
Net Weight	0.02 lb(US) (0.007 kg)			

#### **Environment**

Product Certifications	CSA UL
Protective Treatment	TC
Ambient Air Temperature For Operation	-13158 °F (-2570 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ambient Air Temperature For Storage	-40158 °F (-4070 °C)
Overvoltage Category	Class 3 IEC 60536 Class 3 NF C 20-030

## Ordering and shipping details

Category	US10CS222460
Discount Schedule	0CS2
Gtin	3389110651669
Returnability	Yes
Country Of Origin	US

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	0.63 in (1.6 cm)
Package 1 Width	0.63 in (1.6 cm)
Package 1 Length	1.93 in (4.9 cm)
Package 1 Weight	0.25 oz (7.0 g)
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	1.18 in (3.0 cm)
Package 2 Width	3.54 in (9.0 cm)
Package 2 Length	6.30 in (16.0 cm)
Package 2 Weight	2.57 oz (73.0 g)
Unit Type Of Package 3	S01
Number Of Units In Package 3	100
Package 3 Height	5.91 in (15.0 cm)
Package 3 Width	5.91 in (15.0 cm)
Package 3 Length	15.75 in (40.0 cm)
Package 3 Weight	33.54 oz (951.0 g)

### **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**


Reach Regulation	Pro-active compliance (Product out of EU RoHS legal scope)		
Eu Rohs Directive			
China Rohs Regulation	China RoHS declaration		
Environmental Disclosure	Product Environmental Profile		
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.		
Circularity Profile	No need of specific recycling operations		
California Proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov		

#### XVLA333

**Dimensions Drawings** 

#### **LED Pilot Light**

#### **Dimensions**




- (1) Threaded connector
- e panel thickness: 1 to 8 mm/0.03 to 0.31 in.

#### XVLA333

Mounting and Clearance

#### LED Pilot Light

#### **Panel Drilling**



Ø min		G min		H min	
mm	in.	mm	in.	mm	in.
12.2	0.48	16.5	0.65	16.5	0.65