

Product datasheet

Specifications



50MM OFF-WHITE BASE UNIT

XVPC21W

! Discontinued on: 30 Jun 2015

! End-of-service on: 31 Dec 2015

! Discontinued

Main

Range of product	Harmony XVP Universal
Product or component type	Base unit with cover
Mounting diameter	50 mm
Component name	XVPC
Housing colour	Cream
Connections - terminals	Screw clamp terminals, <= 1 x 1.5 mm² with or without cable end

Complementary

Fixing mode	Direct or tube fixing
Material	Acrylic butadiene styrene + polycarbonate: base unit Polyamide: cover unit
Assembly style	Customer assembly, up to 5 units
Marking	CE
[UI] rated insulation voltage	250 V conforming to IEC 60947-1
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60947-1
Terminals description ISO n°1	(COM-5)PW (GND)GROUND (COM-1)PW (COM-4)PW (COM-2)PW (COM-3)PW
Net weight	0.125 kg

Environment

Product certifications	cULus
Standards	EN/IEC 60947-5-1
Protective treatment	TC
Ambient air temperature for storage	-40...70 °C

Contractual warranty


Warranty	18 months
----------	-----------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Mounting and Clearance

Base Unit for Indicator Banks


Panel Cut-out for Direct Fixing



Connections and Schema

Indicator Bank

Wiring Diagram



- +/1 Power supply for first unit
- +/2 Power supply for second unit
- +/3 Power supply for third unit
- +/4 Power supply for fourth unit
- +/5 Power supply for fifth unit
- /C Common for all units