Product data sheet

Specifications





Rotating beacon, Harmony XVR, 84mm, orange, without buzzer, 24V AC DC

XVR08B05

Product availability: Stock - Normally stocked in distribution

Price*: 180.00 USD

Main

Range Of Product	Harmony XVR
Product Or Component Type	Prewired rotating mirror beacon
Sound Signalling	Without
Device Short Name	XVR
Mounting Diamete	3.31 in (84 mm)
Ip Degree Of Protection	IP65 IEC 60529 with accessory) IP23 IEC 60529
[Us] Rated Supply Voltage	24 V AC/DC
Light Source	High luminosity LED, orange

Complementary

Material	ABS (acrylonitrile butadiene-styrene): body part PC: globe	
Cad Overall Width	3.31 in (84 mm)	
Cad Overall Depth	3.31 in (84 mm)	
Net Weight	0.66 lb(US) (0.3 kg)	
Marking	CE	
Product Mounting	By 3 M4 screws	
Supply Voltage Limits	1930 V DC 21.626.4 V AC	
[Uimp] Rated Impulse Withstand Voltage	0.8 kV	
Current Consumption	125 mA	
Flashing Frequency	2.3 Hz	
Clamping Connection Capacity	0.83 mm²	
Awg Gauge	AWG 18	
Cable Length	19.69 in (500 mm)	

Environment

Standards	IEC 61000-6-4 IEC 61000-6-2
Product Certifications	UL
Protective Treatment	TC

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ambient Air Temperature For Storage	-31158 °F (-3570 °C)
Ambient Air Temperature For Operation	14122 °F (-1050 °C)
Electrical Shock Protection Class	Class II IEC 61140

Ordering and shipping details

Category	US100XV22617
Discount Schedule	00XV
Gtin	3606480033001
Returnability	Yes
Country Of Origin	ID

Packing Units

•	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.68 in (19.5 cm)
Package 1 Width	3.94 in (10.0 cm)
Package 1 Length	3.94 in (10.0 cm)
Package 1 Weight	13.86 oz (393.0 g)
Unit Type Of Package 2	S03
Number Of Units In Package 2	6
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	6.73 lb(US) (3.051 kg)

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Rohs Exemption Information

Certifications & Standards


Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov


XVR08B05

Dimensions Drawings

Rotating Mirror Beacon

Dimensions





Product data sheet

XVR08B05

Mounting and Clearance

Rotating Mirror Beacon

Panel Cut-out

