# Product data sheet

Specifications





## Prewired rotating mirror beacon, Harmony XVR, 106mm, orange, without buzzer, 24V AC/DC

XVR10B05

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 207.00 USD

### Main

Range Of Product	Harmony XVR
Product Or Component Type	Prewired rotating mirror beacon
Sound Signalling	Without
Device Short Name	XVR
Mounting Diamete	4.17 in (106 mm)
Ip Degree Of Protection	IP55 IEC 60529 with accessory) IP23 IEC 60529
[Us] Rated Supply Voltage	24 V AC/DC
Light Source	High luminosity LED, orange

### Complementary

Material	ABS (acrylonitrile butadiene-styrene): body part PMMA (polymethyl methacrylate): globe
Cad Overall Width	4.17 in (106 mm)
Cad Overall Depth	4.17 in (106 mm)
Net Weight	1.10 lb(US) (0.5 kg)
Marking	CE
Product Mounting	By 3 M4 screws
Supply Voltage Limits	1930 V DC 21.626.4 V AC
[Uimp] Rated Impulse Withstand Voltage	0.8 kV
Current Consumption	125 mA
Flashing Frequency	2.3 Hz
Clamping Connection Capacity	0.83 mm²
Awg Gauge	AWG 18
Cable Length	15.75 in (400 mm)

#### **Environment**

Standards	IEC 61000-6-2 IEC 61000-6-4
Product Certifications	UL
Protective Treatment	TC

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ambient Air Temperature For Storage	-31158 °F (-3570 °C)
Ambient Air Temperature For Operation	14122 °F (-1050 °C)
Electrical Shock Protection Class	Class II IEC 61140

# Ordering and shipping details

	· · · -
Category	US100XV22617
Discount Schedule	00XV
Gtin	3606480033087
Returnability	No
Country Of Origin	US

# **Packing Units**

_	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.51 in (14.0 cm)
Package 1 Width	5.51 in (14.0 cm)
Package 1 Length	7.68 in (19.5 cm)
Package 1 Weight	22.01 oz (624.0 g)
Unit Type Of Package 2	S04
Number Of Units In Package 2	8
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	15.75 in (40.0 cm)
Package 2 Length	23.62 in (60.0 cm)
Package 2 Weight	14.05 lb(US) (6.372 kg)

## **Contractual warranty**

Warranty 18 months



Green Premium<sup>TM</sup> label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance



Rohs Exemption Information

#### **Certifications & Standards**


Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov


### XVR10B05

### **Dimensions Drawings**

## Rotating Mirror Beacon

#### **Dimensions**





## **Product data sheet**

### XVR10B05

Mounting and Clearance

### Rotating Mirror Beacon

#### **Panel Cut-out**

