Product data sheet

Specifications





Rotating beacon, Harmony XVR, 120mm, red, with buzzer 50... 90dB, 24V AC DC

XVR12B04S

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 216.00 USD

Main

| Range Of Product | Harmony XVR | |
|---------------------------|---|--|
| Product Or Component Type | Prewired rotating mirror beacon | |
| Sound Signalling | Buzzer | |
| Device Short Name | XVR | |
| Mounting Diameter | 4.72 in (120 mm) | |
| Ip Degree Of Protection | IP23 IEC 60529 | |
| [Us] Rated Supply Voltage | 24 V AC/DC | |
| Light Source | High luminosity LED, red | |
| Noise Level | 5090 dB continuous or intermittent tone)1 m | |

Complementary

| ABS (acrylonitrile butadiene-styrene): body part AS: globe | |
|---|--|
| 4.72 in (120 mm) | |
| 4.72 in (120 mm) | |
| 1.10 lb(US) (0.5 kg) | |
| CE | |
| By 3 M5 screws | |
| 1930 V DC 21.626.4 V AC | |
| 0.8 kV | |
| 196 mA | |
| 2.3 Hz | |
| 0.83 mm² | |
| AWG 18 | |
| 15.75 in (400 mm) | |
| | |

Environment

| Standards | IEC 61000-6-4 IEC 61000-6-2 |
|----------------------|--------------------------------|
| Protective Treatment | тс |

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

| Ambient Air Temperature For Storage | -31158 °F (-3570 °C) |
|--|----------------------|
| Ambient Air Temperature For Operation | 14122 °F (-1050 °C) |
| Electrical Shock Protection Class | Class II IEC 61140 |

Ordering and shipping details

| Category | US100XV22617 | |
|-------------------|---------------|--|
| Discount Schedule | 00XV | |
| Gtin | 3606480033230 | |
| Returnability | Yes | |
| Country Of Origin | ID | |

Packing Units

| Unit Type Of Package 1 | PCE | |
|------------------------------|-------------------------|--|
| Number Of Units In Package 1 | 1 | |
| Package 1 Height | 7.68 in (19.500 cm) | |
| Package 1 Width | 5.43 in (13.800 cm) | |
| Package 1 Length | 5.51 in (14.000 cm) | |
| Package 1 Weight | 23.46 oz (665.000 g) | |
| Unit Type Of Package 2 | S04 | |
| Number Of Units In Package 2 | 8 | |
| Package 2 Height | 11.81 in (30.000 cm) | |
| Package 2 Width | 15.75 in (40.000 cm) | |
| Package 2 Length | 23.62 in (60.000 cm) | |
| Package 2 Weight | 14.38 lb(US) (6.522 kg) | |

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Rohs Exemption Information


Certifications & Standards

| Reach Regulation | REACh Declaration |
|---------------------------|--|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

Dimensions Drawings

Rotating Mirror Beacon

Dimensions



<u>3xM5</u>

0.71

Product data sheet

Mounting and Clearance

Rotating Mirror Beacon

Panel Cut-out

