



130mm Rotating Mirror Orange 230VAC IP67

XVR13M05L

Main

| Range of product | Harmony XVR |
|---------------------------|--|
| Product or component type | Prewired rotating mirror beacon |
| Sound signalling | Without |
| Device short name | XVR |
| Mounting diameter | 130 mm |
| IP degree of protection | IP66 conforming to IEC 60529 IP67 conforming to IEC 60529 |
| [Us] rated supply voltage | 230 V AC |
| Light source | High luminosity LED, orange |

Complementary

| Material | ABS (acrylonitrile butadiene-styrene): body part PC: globe |
|--|--|
| CAD overall width | 130 mm |
| CAD overall depth | 130 mm |
| Net weight | 0.99 kg |
| Marking | CE |
| Product mounting | By 3 M6 screws |
| [Uimp] rated impulse withstand voltage | 4 kV |
| Current consumption | 22 mA |
| Flashing frequency | 2.7 Hz |
| Clamping connection capacity | 1.25 mm² |
| AWG gauge | AWG 18 |
| Cable length | 400 mm |

Environment

| Standards | EN/IEC 60947-1 EN/IEC 60947-5-1 |
|---------------------------------------|------------------------------------|
| protective treatment | TC |
| ambient air temperature for storage | -3570 °C |
| Ambient air temperature for operation | -3050 °C |
| Electrical shock protection class | Class II conforming to IEC 61140 |

Packing Units

| • | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 19.500 cm |
| Package 1 Width | 19.500 cm |
| Package 1 Length | 26.500 cm |
| Package 1 Weight | 1.340 kg |
| Unit Type of Package 2 | S04 |
| Number of Units in Package 2 | 6 |
| Package 2 Height | 30.000 cm |
| Package 2 Width | 40.000 cm |
| Package 2 Length | 60.000 cm |
| Package 2 Weight | 9.102 kg |
| Unit Type of Package 3 | P06 |
| Number of Units in Package 3 | 24 |
| Package 3 Height | 75.000 cm |
| Package 3 Width | 60.000 cm |
| Package 3 Length | 80.000 cm |
| Package 3 Weight | 45.668 kg |

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Rohs Exemption Information

Certifications & Standards


| Reach Regulation | REACh Declaration |
|--------------------------|--|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |


XVR13M05L

Dimensions Drawings

Rotating Mirror Beacon

Dimensions





Product datasheet

XVR13M05L

Mounting and Clearance

Rotating Mirror Beacon

Panel Cut-out

