

Product data sheet

Specifications



Multisound siren, Harmony XVS,
prewired, white colour, 0...105dB,
43tones, 12...24V DC

XVS14BMW

Product availability: Stock - Normally stocked in distribution facility

Price*: 360.00 USD

Main

Range Of Product	Harmony XVS
Product Or Component Type	Multisound siren
Device Short Name	XVS

Complementary

Color	White
Material	ASA (Acrylonitrile Styrene Acrylate): front ASA (Acrylonitrile Styrene Acrylate): back PC (polycarbonate): back cover
Net Weight	2.20 lb(US) (1 kg)
Marking	CE
Mounting Support	Bracket
Fixing Mode	3 holes Ø 9 mm
[Uimp] Rated Impulse Withstand Voltage	0.8 kV
Current Consumption	350 mA 24 V 250 mA 12 V
Electrical Connection	Cable 0.26...0.33 in (6.5...8.5 mm), 0.00 in² (0.33 mm²) / AWG 22 signalling circuit Cable 0.26...0.33 in (6.5...8.5 mm), 0.00 in² (0.52 mm²) / AWG 20 power circuit
Width	5.51 in (140 mm)
Height	4.49 in (114 mm)
Depth	8.78 in (223 mm)

Environment

Signalling Type	43 tones siren
Standards	IEC 61000-6-2 EN 55014-2 EN 55022 IEC 61000-6-3
Product Certifications	UL
Protective Treatment	TC
Ambient Air Temperature For Storage	-31...158 °F (-35...70 °C)
Ambient Air Temperature For Operation	14...122 °F (-10...50 °C)
Overvoltage Category	Class II IEC 61140

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ip Degree Of Protection	IP53 conforming to IEC 60529
[Us] Rated Supply Voltage	12 V DC 24 V DC
Noise Level	0...105 dB continuous or intermittent tone)1 m

Ordering and shipping details

Category	US100XV22617
Discount Schedule	00XV
Gtin	3606480032943
Returnability	Yes
Country Of Origin	US

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	11.81 in (30 cm)
Package 1 Width	7.09 in (18 cm)
Package 1 Length	7.28 in (18.5 cm)
Package 1 Weight	2.88 lb(US) (1.307 kg)
Unit Type Of Package 2	S04
Number Of Units In Package 2	6
Package 2 Height	11.81 in (30 cm)
Package 2 Width	15.75 in (40 cm)
Package 2 Length	23.62 in (60 cm)
Package 2 Weight	20.05 lb(US) (9.094 kg)
Unit Type Of Package 3	PAL
Number Of Units In Package 3	24
Package 3 Height	23.62 in (60 cm)
Package 3 Width	31.50 in (80 cm)
Package 3 Length	9.45 in (24 cm)
Package 3 Weight	72.81 lb(US) (33.024 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation

[China RoHS declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

[End of Life Information](#)

California Proposition 65

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Dimensions Drawings

Siren

Dimensions

