Product data sheet

Specification





Electronic alarm, Harmony XVS, black, NPN, mounting support DIN 72, 0...90dB, 16tones, 4 channels, 12...24V AC DC

XVS72BMBN

Product availability: Stock - Normally stocked in distribution facility

Price*: 180.00 USD

Main

| Range Of Product | Harmony XVS | |
|---------------------------|------------------|--|
| Product Or Component Type | Electronic alarm | |
| Device Short Name | XVS | |

Complementary

| Color | Black | |
|--|--|--|
| Material | ABS (acrylonitrile butadiene-styrene): body PC (polycarbonate): terminal cover | |
| Marking | CE | |
| Overvoltage Category | Class II IEC 61140 | |
| Mounting Support | 72 mm DIN rail | |
| [Us] Rated Supply Voltage | 1224 V DC | |
| [Uimp] Rated Impulse Withstand Voltage | 0.8 kV | |
| Current Consumption | 117 mA 12 V 125 mA 24 V 158 mA 12 V 200 mA 24 V | |
| Clamping Connection Capacity | <= 1 x 1.5 mm² | |
| Width | 2.83 in (72 mm) | |
| Height | 2.83 in (72 mm) | |
| Depth | 2.73 in (69.3 mm) | |
| Net Weight | 0.40 lb(US) (0.18 kg) | |

Environment

| Discrete Output Type | NPN |
|-------------------------------------|--|
| Signalling Type | 16 tones alarm |
| Standards | UL 464 IEC 61000-6-3 IEC 61000-6-2 |
| Product Certifications | UR |
| Protective Treatment | TC |
| Ambient Air Temperature For Storage | -31158 °F (-3570 °C) |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Ambient Air Temperature For Operation | 14122 °F (-1050 °C) |
|---------------------------------------|---|
| Ip Degree Of Protection | Panel mounted IP54 IEC 60529 |
| Noise Level | 0 90 dB continuous or intermittent tone)1 m |

Ordering and shipping details

| Category | US100XV22617 | |
|-------------------|---------------|--|
| Discount Schedule | 00XV | |
| Gtin | 3606480032929 | |
| Returnability | Yes | |
| Country Of Origin | ID | |

Packing Units

| Unit Type Of Package 1 | PCE | |
|------------------------------|-------------------------|--|
| Number Of Units In Package 1 | 1 | |
| Package 1 Height | 3.70 in (9.4 cm) | |
| Package 1 Width | 3.70 in (9.4 cm) | |
| Package 1 Length | 4.10 in (10.41 cm) | |
| Package 1 Weight | 0.60 lb(US) (0.27 kg) | |
| Unit Type Of Package 2 | S03 | |
| Number Of Units In Package 2 | 16 | |
| Package 2 Height | 11.81 in (30 cm) | |
| Package 2 Width | 11.81 in (30 cm) | |
| Package 2 Length | 15.75 in (40 cm) | |
| Package 2 Weight | 11.28 lb(US) (5.118 kg) | |
| Unit Type Of Package 3 | PAL | |
| Number Of Units In Package 3 | 128 | |
| Package 3 Height | 23.62 in (60 cm) | |
| Package 3 Width | 31.50 in (80 cm) | |
| Package 3 Length | 50.39 in (128 cm) | |
| Package 3 Weight | 76.19 lb(US) (34.56 kg) | |
| | | |

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

| Reach Regulation | REACh Declaration |
|---------------------------|---|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

Product data sheet

XVS72BMBN

Dimensions Drawings

Electronic Alarm

Dimensions

