# **Product datasheet**

Specifications





# Single contact block with body/ fixing collar, metal, screw clamp terminal, 1 NC

Local distributor code: 23707348

ZB4BZ102

EAN Code: 3389110889383

#### Main

Range Of Product	Harmony XB4	
Product Or Component Type	Complete body/contact assembly	
Device Short Name	ZB4	
Fixing Collar Material	Zamak	
Sale Per Indivisible Quantity	1	
Head Type	Standard	
Contacts Type And Composition	1 NC	
Contact Operation	Slow-break	
Contact Block Type	Single	
Device Composition	Body Fixing collar	
Connections - Terminals	Screw clamp terminals, <= 2 x 1.5 mm² with cable end conforming to IEC 60947-1 Screw clamp terminals, >= 1 x 0.22 mm² without cable end conforming to IEC 60947-1	

### Complementary

,		
Cad Overall Width	30 mm	
Cad Overall Height	47 mm	
Cad Overall Depth	37 mm	
Terminals Description Iso N°1	(11-12)NC	
Net Weight	0.053 kg	
Contacts Usage	Standard contacts	
Positive Opening	With conforming to IEC 60947-5-1 appendix K	
Operating Travel	1.5 mm (NC changing electrical state) 4.3 mm (total travel)	
Operating Force	2 N NC changing electrical state	
Mechanical Durability	5000000 cycles	
Tightening Torque	0.81.2 N.m conforming to IEC 60947-1	
Shape Of Screw Head	Head  Cross compatible with Philips no 1 screwdriver  Cross compatible with pozidriv No 1 screwdriver  Slotted compatible with flat Ø 4 mm screwdriver  Slotted compatible with flat Ø 5.5 mm screwdriver	
Contacts Material	Silver alloy (Ag/Ni)	
Short-Circuit Protection	10 A cartridge fuse type gG conforming to IEC 60947-5-1	

[Ith] Conventional Free Air Thermal Current	10 A conforming to IEC 60947-5-1	
[Ui] Rated Insulation Voltage	600 V (pollution degree 3) conforming to IEC 60947-1 6 kV conforming to IEC 60947-1	
[Uimp] Rated Impulse Withstand Voltage		
[le] Rated Operational Current	3 A at 240 V, AC-15, A600 conforming to IEC 60947-5-1 6 A at 120 V, AC-15, A600 conforming to IEC 60947-5-1 0.1 A at 600 V, DC-13, Q600 conforming to IEC 60947-5-1 0.27 A at 250 V, DC-13, Q600 conforming to IEC 60947-5-1 0.55 A at 125 V, DC-13, Q600 conforming to IEC 60947-5-1 1.2 A at 600 V, AC-15, A600 conforming to IEC 60947-5-1	
Electrical Durability	10000000 cycles, AC-15, 2 A at 230 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 10000000 cycles, AC-15, 3 A at 120 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 10000000 cycles, AC-15, 4 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 10000000 cycles, DC-13, 0.2 A at 110 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 10000000 cycles, DC-13, 0.5 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C	
Electrical Reliability	$\Lambda$ < 10exp(-6) at 5 V, 1 mA in clean environment conforming to IEC 60947-5-4 $\Lambda$ < 10exp(-8) at 17 V, 5 mA in clean environment conforming to IEC 60947-5-4	
Device Presentation	Basic sub-assemblies	

### **Environment**

Protective Treatment	тн	
Ambient Air Temperature For Storage	-4070 °C	
Ambient Air Temperature For Operation	-4070 °C	
Ip Degree Of Protection	IP20 conforming to IEC 60529	
Standards	CSA C22.2 No 14 IEC 60947-5-5 IEC 60947-5-1 UL 508 JIS C8201-5-1 IEC 60947-1 IEC 60947-5-4 JIS C8201-1	
Product Certifications	BV GL CSA LROS (Lloyds register of shipping) UL DNV	
Vibration Resistance	5 gn (f= 2500 Hz) conforming to IEC 60068-2-6	
Shock Resistance	30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27	

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.400 cm
Package 1 Width	3.400 cm
Package 1 Length	5.400 cm
Package 1 Weight	52.000 g

Unit Type Of Package 2	BB1
Number Of Units In Package 2	5
Package 2 Height	4.400 cm
Package 2 Width	3.400 cm
Package 2 Length	26.500 cm
Package 2 Weight	260.000 g
Unit Type Of Package 3	S03
Number Of Units In Package 3	200
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	10.920 kg

# **Contractual warranty**

Warranty 18 months

## Sustainability Green Premium\*

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>⊘</b>	Reach Free Of Svhc	
<b>⊘</b>	Toxic Heavy Metal Free	
<b>⊘</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**


Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

### **Product datasheet**

### **ZB4BZ102**

### **Dimensions Drawings**

#### **Dimensions**




#### **ZB4BZ102**


#### Mounting and Clearance

Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)

Connection by Screw Clamp Terminals or Plug-in Connectors or on Printed Circuit Board

**Connection by Faston Connectors** 





- (1) Diameter on finished panel or support
- (2) 40 mm min. / 1.57 in. min.
- (3) 30 mm min. / 1.18 in. min.
- (4) Ø 22.5 mm / 0.89 in. recommended (Ø 22.3 mm  $_0^{+0.4}$  / 0.88 in.  $_0^{+0.016}$ )
- (5) 45 mm min. / 1.78 in. min.
- (6) 32 mm min. / 1.26 in. min.