Product data sheet

Specifications





green flush/red projecting/green flush triple-headed pushbutton Ø22 with marking

ZB5AA73135

! Discontinued on: Dec 2, 2020

! End-of-service on: Dec 31, 2020

① Discontinued

Main

Range of Product	Harmony XB5	
Product or Component Type	Head for triple-headed push-button	
Device short name	XB5	
Bezel material	Dark grey plastic	
Mounting diameter	0.9 in (22 mm)	
Head type	Standard	
Shape of signaling unit head	Rectangular	
Type of operator	spring return	
Operator profile	2 flush - 1 central projecting STOP push-buttons	
Operators description	Green "+" - green "-" - red "STOP"	

Complementary

CAD overall width	1.2 in (30 mm)
CAD overall height	2.0 in (50 mm)
CAD overall depth	1.4 in (35 mm)
Product Weight	0.051 lb(US) (0.023 kg)
Resistance to high pressure washer	1015.3 psi (7000000 Pa) 131.0000000000 °F (55 °C) 0.1 m
Colour of marking	Black marking when white caps White marking when green, red or black caps
Operator profile	Red projecting, STOP white) Green flush, - white) Green flush, + white)
Mechanical durability	1000000 cycles
Station name	XALD 1 cut-out
Electrical composition code	C1 9 single front mounting C2 9 single and double front mounting C11 3 single front mounting SF1 3 single front mounting SR1 3 single rear mounting
device presentation	Basic element

Environment

Ambient Air Temperature for	-40.0000000000158.0000000000 °F (-4070 °C)	
Storage		

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Sep 9, 2024 Life Is On Schneider

Ambient Air Temperature for Operation	-13.0000000000158.00000000000 °F (-2570 °C)	
Electrical shock protection class	Class II IEC 61140	
IP degree of protection	IP67 IEC 60529 IP69 IEC 60529 IP69K	
NEMA degree of protection	NEMA 13 NEMA 4X	
IK degree of protection	IK05 conforming to IEC 50102	
Standards	EN/IEC 60947-5-4 UL 508 JIS C8201-5-1 CSA C22.2 No 14 EN/IEC 60947-1 EN/IEC 60947-5-1 JIS C8201-1	
Product Certifications	BV CSA UL Listed GL DNV LROS (Lloyds register of shipping)	
Vibration resistance	5 gn 2500 Hz)IEC 60068-2-6	
Shock resistance	30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27	

Ordering and shipping details

Category	22467-PUSHBUTTONS,22MM(PLASTIC) NEW	
Discount Schedule	CS2	
GTIN	03389119043458	
Returnability	No	
Country of origin	FR	

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Reach Free Of Svhc	
②	Toxic Heavy Metal Free	
②	Mercury Free	
	Rohs Exemption Information	Yes

Certifications & Standards

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov