Product datasheet

Specifications





Head for push button, Harmony XB5, XB4, pushbutton harsh environment, white, without marking

ZB5AC180

Main

Range of product	Harmony XB5	
product or component type	Head for push-button	
Device short name	ZB5	
Bezel material	Black plastic	
Head type	Standard	
Mounting diameter	22 mm	
Sale per indivisible quantity	1	
Shape of signaling unit head	Round	
Type of operator	spring return	
Operator additional information	Vertical mounting Horizontal mounting	

Complementary

CAD overall width	37 mm	
CAD overall height	18.5 mm	
CAD overall depth	37 mm	
net weight	0.024 kg	
Resistance to high pressure washer	90 Pa at 82.5 °C	
Operator profile	White flush, unmarked	
Mechanical durability	10000000 cycles	
Electrical composition code	C1 for <9 contacts using single blocks in front mounting C2 for <9 contacts using single and double blocks in front mounting C11 for <3 contacts using single blocks in front mounting C15 for <1 contacts using single blocks in front mounting SF1 for <3 contacts using single blocks in front mounting SR1 for <3 contacts using single blocks in rear mounting	
device presentation	Basic element	

Environment

Ambient air temperature for storage	-4085 °C	
Ambient air temperature for operation	-4070 °C	
Electrical shock protection class	Class II conforming to IEC 61140	
IP degree of protection	IP66 conforming to IEC 60529 IP69K IP67	

11-Jul-2024 Life Is On Schneider

NEMA degree of protection	NEMA 4 conforming to UL 508 NEMA 13 NEMA 12	
IK degree of protection	IK03 conforming to IEC 62262	
Standards	UL 508 IEC 60947-5-1 IEC 60947-1 CSA C22.2	
Product certifications	CSA UL CE	
Vibration resistance	ion resistance 5 gn (f= 2500 Hz) conforming to IEC 60068-2-6	
Shock resistance 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IE 60068-2-27		

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.7 cm
Package 1 Width	3.7 cm
Package 1 Length	3.7 cm
Package 1 Weight	24.0 g

Contractual warranty

Warranty 18 months

11-Jul-2024



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance


②	Reach Free Of Svhc	
②	Toxic Heavy Metal Free	
②	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Dimensions Drawings


Dimensions



Mounting and Clearance


Installation on Flat Surface

Without Protective Guard



(1) Ø22.5 mm recommended (Ø22.3 $_0^{+0.4}$) / Ø0.89 in. recommended (Ø0.88 $_0^{+0.016}$)

With Protective Guard



(1) Ø22.5 mm recommended (Ø22.3 $_0^{+0.4}$) / Ø0.89 in. recommended (Ø0.88 $_0^{+0.016}$)

Product datasheet

ZB5AC180

Technical Description

Electrical Composition Corresponding to Code C1



Electrical Composition Corresponding to Code C2



Product datasheet

ZB5AC180

Electrical Composition Corresponding to Codes C9, C11, SF1 and SR1



Electrical Composition Corresponding to Code C15





1 N/C



1 N/O + N/C or 1 N/O + N/O or 1 N/C + N/C



Legend

Single contact



Double contact



Light block



Possible location

