# **Product datasheet**

Specification





Head for double headed push button, Harmony XB5, 1 green flush, 1 red projecting, 22mm, spring return, unmarked

ZB5AL7340

### Main

Range of product	Harmony XB5	
product or component type	Head for double-headed push-button	
Device short name	ZB5	
Bezel material	Dark grey plastic	
Mounting diameter	22 mm	
Head type	Standard	
Sale per indivisible quantity	1	
Shape of signaling unit head	Rectangular	
Type of operator	spring return	
Operator profile	1 flush - 1 projecting push-buttons	
Operators description	Green unmarked - red unmarked	

### Complementary

CAD overall width	30 mm	
CAD overall height	50 mm	
CAD overall depth	35 mm	
net weight	0.023 kg	
Colour of marking	White marking when green, red or black caps Black marking when white caps	
Operator profile	Green flush, unmarked Red projecting, unmarked	
Mechanical durability	1000000 cycles	
Station name	XALD 1 cut-out	
Electrical composition code	C3 for <6 contacts using single blocks in front mounting C4 for <6 contacts using single and double blocks in front mounting C14 for <2 contacts using single blocks in front mounting SF2 for <2 contacts using single blocks in front mounting SR2 for <2 contacts using single blocks in rear mounting	
device presentation	Basic element	

#### **Environment**

protective treatment	тн
Ambient air temperature for storage	-4070 °C
Ambient air temperature for operation	-2570 °C

Electrical shock protection class	Class II conforming to IEC 60536	
IP degree of protection	IP66 conforming to IEC 60529 IP69K conforming to IEC 60529	
NEMA degree of protection	NEMA 13 NEMA 4X	
Resistance to high pressure washer	7000000 Pa at 55 °C, distance : 0.1 m	
IK degree of protection	IK03 conforming to IEC 50102	
Standards	EN/IEC 60947-5-4 EN/IEC 60947-5-1 JIS C8201-5-1 EN/IEC 60947-1 UL 508 CSA C22.2 No 14 JIS C8201-1	
Product certifications	BV DNV CSA GL LROS (Lloyds register of shipping) UL listed	
Vibration resistance	5 gn (f= 2500 Hz) conforming to IEC 60068-2-6	
Shock resistance	30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27	

## **Packing Units**

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	3.3 cm
Package 1 Length	5.3 cm
Package 1 Weight	25.0 g
Unit Type of Package 2	S01
Number of Units in Package 2	75
Package 2 Height	15.0 cm
Package 2 Width	15.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	2.1 kg

### **Contractual warranty**

Warranty 18 months



**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

	Reach Free Of Svhc	
<b>⊘</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information