Product data sheet

Specifications





Head for double headed push button, Harmony XB5, plastic, 22mm, 1 green flush marked I + 1 red projecting marked O

ZB5AL7341

Product availability: Stock - Normally stocked in distribution facility

Price*: 39.50 USD

Main

Range of Product	Harmony XB5	
Product or Component Type	Head for double-headed push-button	
Device short name	ZB5	
Bezel material	Dark grey plastic	
Mounting diameter	0.9 in (22 mm)	
Head type	Standard	
Sale per indivisible quantity	1	
Shape of signaling unit head	Rectangular	
Type of operator	spring return	
Operator profile	1 flush - 1 projecting push-buttons	
Operators description	Green "I" - red "O"	

Complementary

CAD overall width 1.2 in (30 mm) CAD overall height 2.0 in (50 mm) CAD overall depth 1.4 in (35 mm) Product Weight 0.051 lb(US) (0.023 kg) Colour of marking White marking when green, red or black caps Black marking when white caps Operator profile Green flush, I white) Red projecting, O white) Mechanical durability 1000000 cycles Station name XALD 1 cut-out Electrical composition code C3 6 single front mounting C14 2 single front mounting SF2 2 single rear mounting SF2 2 single rear mounting device presentation Basic element	· · · · · · · · · · · · · · · · · · ·	
CAD overall depth 1.4 in (35 mm) Product Weight 0.051 lb(US) (0.023 kg) Colour of marking White marking when green, red or black caps Black marking when white caps Operator profile Green flush, I white) Red projecting, O white) Mechanical durability 1000000 cycles Station name XALD 1 cut-out Electrical composition code C3 6 single front mounting C14 2 single front mounting SF2 2 single rear mounting	CAD overall width	1.2 in (30 mm)
Product Weight 0.051 lb(US) (0.023 kg) Colour of marking White marking when green, red or black caps Black marking when white caps Operator profile Green flush, I white) Red projecting, O white) Mechanical durability 1000000 cycles Station name XALD 1 cut-out Electrical composition code C3 6 single front mounting C4 6 single and double front mounting SF2 2 single front mounting SF2 2 single rear mounting	CAD overall height	2.0 in (50 mm)
Colour of marking White marking when green, red or black caps Black marking when white caps Operator profile Green flush, I white) Red projecting, O white) Mechanical durability 1000000 cycles Station name XALD 1 cut-out Electrical composition code C3 6 single front mounting C4 6 single and double front mounting SF2 2 single front mounting SF2 2 single rear mounting	CAD overall depth	1.4 in (35 mm)
Black marking when white caps Operator profile Green flush, I white) Red projecting, O white) Mechanical durability 1000000 cycles Station name XALD 1 cut-out Electrical composition code C3 6 single front mounting C4 6 single and double front mounting C14 2 single front mounting SF2 2 single front mounting SF2 2 single rear mounting	Product Weight	0.051 lb(US) (0.023 kg)
Red projecting, O white) Mechanical durability 1000000 cycles Station name XALD 1 cut-out Electrical composition code C3 6 single front mounting C4 6 single and double front mounting C14 2 single front mounting SF2 2 single front mounting SR2 2 single rear mounting	Colour of marking	
Station name XALD 1 cut-out Electrical composition code C3 6 single front mounting C4 6 single and double front mounting C14 2 single front mounting SF2 2 single front mounting SR2 2 single rear mounting	Operator profile	
Electrical composition code C3 6 single front mounting C4 6 single and double front mounting C14 2 single front mounting SF2 2 single front mounting SR2 2 single rear mounting	Mechanical durability	1000000 cycles
C4 6 single and double front mounting C14 2 single front mounting SF2 2 single front mounting SR2 2 single rear mounting	Station name	XALD 1 cut-out
device presentation Basic element	Electrical composition code	C4 6 single and double front mounting C14 2 single front mounting SF2 2 single front mounting
	device presentation	Basic element

Environment

protective treatment

TH

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Ambient Air Temperature for Storage	-40.000000000158.0000000000 °F (-4070 °C)
Ambient Air Temperature for Operation	-13.000000000158.0000000000 °F (-2570 °C)
Electrical shock protection class	Class II IEC 60536
IP degree of protection	IP66 IEC 60529 IP69K IEC 60529
NEMA degree of protection	NEMA 13 NEMA 4X
Resistance to high pressure washer	1015.3 psi (7000000 Pa) 131.0000000000 °F (55 °C) 0.1 m
IK degree of protection	IK03 conforming to IEC 50102
Standards	IEC 60947-5-4 IEC 60947-1 CSA C22.2 No 14 IEC 60947-5-1 JIS C8201-5-1 UL 508 JIS C8201-1
Product Certifications	GL BV LROS (Lloyds register of shipping) CSA DNV UL Listed
Vibration resistance	5 gn 2500 Hz)IEC 60068-2-6
Shock resistance	30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27

Ordering and shipping details

Category	US10CS222467	
Discount Schedule	0CS2	
GTIN	3389119043311	
Returnability	Yes	
Country of origin	FR	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.2 in (5.5 cm)
Package 1 Width	1.3 in (3.3 cm)
Package 1 Length	2.09 in (5.3 cm)
Package 1 Weight	0.9 oz (26.0 g)
Unit Type of Package 2	S03
Number of Units in Package 2	200
Package 2 Height	11.8 in (30 cm)
Package 2 Width	11.8 in (30 cm)
Package 2 Length	15.7 in (40 cm)
Package 2 Weight	12.659 lb(US) (5.742 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

Certifications & Standards

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov