# Product data sheet

Specifications





Head for illuminated push button, Harmony XB5, XB4, orange projecting pushbutton 22mm spring return BA9s bulb

ZB5AW15

Product availability: Stock - Normally stocked in distribution facility

Price\*: 13.00 USD

#### Main

Range of Product	Harmony XB5	
Product or Component Type	Head for illuminated push-button	
Device short name	ZB5	
Product Compatibility	BA 9s	
Bezel material	Dark grey plastic	
Mounting diameter	0.9 in (22 mm)	
Sale per indivisible quantity	1	
Head type	Standard	
Shape of signaling unit head	Round	
Type of operator	spring return	
Operator profile	Orange projecting, unmarked	
Operator additional information	With plain lens	

### Complementary

CAD overall width	1.1 in (29 mm)	
CAD overall height	1.1 in (29 mm)	
CAD overall depth	1.3 in (32 mm)	
Net Weight	0.037 lb(US) (0.017 kg)	
Resistance to high pressure washer	1015.3 psi (7000000 Pa) 131.00000000000 °F (55 °C) 0.1 m	
Mechanical durability	10000000 cycles	
Main group	Illum push-button	
Group of product	Projected push BA9s	
Station name	XALD 15 cut-outs XALK 25 cut-outs	
Cap/operator or lens colour	Orange	
Marking	Unmarked	
Electrical composition code	M7 6 single front mounting BA 9s M8 6 single and double front mounting BA 9s M9 2 single front mounting BA 9s and transformer	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

MF2 2 single front mounting BA 9s

Device presentation Basic sub-assemblies

#### **Environment**

protective treatment	TC	
Ambient Air Temperature for Storage	-40.0000000000158.0000000000 °F (-4070 °C)	
Ambient Air Temperature for Operation	-40.0000000000131.0000000000 °F (-4055 °C)	
Overvoltage category	Class II IEC 60536	
IP degree of protection	IP66 IEC 60529 IP69 IP69K	
NEMA degree of protection	NEMA 13 NEMA 4X	
IK degree of protection	IK05 conforming to IEC 62262	
Standards	IEC 60947-5-1 GB 14048.5 CSA C22.2 No 14 IEC 60947-5-4 UL 508 IEC 60947-1 JIS C8201-5-1 JIS C8201-1	
Product Certifications	LROS (Lloyds register of shipping) UL Listed BV DNV CSA GL	
Vibration resistance	5 gn 2500 Hz)IEC 60068-2-6	
Shock resistance	30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27	

## Ordering and shipping details

Category	US10CS222467	
Discount Schedule	0CS2	
GTIN	3389110909876	
Returnability	Yes	
Country of origin	CZ	

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.1 in (5.4 cm)
Package 1 Width	1.3 in (3.4 cm)
Package 1 Length	1.7 in (4.4 cm)
Package 1 Weight	0.6 oz (17.0 g)

### **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California Proposition 65	"WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov"