## Product data sheet

Specifications





Head for illuminated push button, Harmony XB5, plastic, orange mushroom 40mm, 22mm, latching turn to release, clear boot

ZB5AW753

Product availability: Non-Stock - Not normally stocked in distribution facility

Important message: A change in appearance may be noted on the product but does not affect its use in terms of function and safety. This makes it compatible with our Universal LED blocks

Price\*: 63.00 USD

#### Main

Range of Product	Harmony XB5	
Product or Component Type	Head for illuminated push-button	
Device short name	ZB5	
Product Compatibility	Universal LED	
Bezel material	Dark grey plastic	
Mounting diameter	0.9 in (22 mm)	
Sale per indivisible quantity	1	
Head type	Standard	
Shape of signaling unit head	Round	
Type of operator	latching	
Reset	Turn to release	
Operator profile	Orange mushroom Ø 40 mm, unmarked	

#### Complementary

CAD overall width	1.6 in (40 mm)	
CAD overall height	1.6 in (40 mm)	
CAD overall depth	2.0 in (50 mm)	
Net Weight	0.049 lb(US) (0.022 kg)	
Resistance to high pressure washer	1015.3 psi (7000000 Pa) 131.00000000000 °F (55 °C) 0.1 m	
Mechanical durability	300000 cycles	
Main group	Mushroom head	
Group of product	Mush. turn to release illum	
Station name	XALD 1 cut-out XALK 1 cut-out	
Cap/operator or lens colour	Orange	
Marking	Unmarked	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Electrical composition code	M6 2 single front mounting integral LED and transformer M10 2 single front mounting integral LED MF1 2 single front mounting integral LED MR1 2 single rear mounting integral LED M3 4 single front mounting integral LED M4 4 single and double front mounting integral LED
Device presentation	Basic sub-assemblies

### **Environment**

Ziivii Oiliiloitt	
protective treatment	TC
Ambient Air Temperature for Storage	-40.0000000000158.0000000000 °F (-4070 °C)
Ambient Air Temperature for Operation	-40.0000000000158.0000000000 °F (-4070 °C)
Overvoltage category	Class II IEC 60536
IP degree of protection	IP66 IEC 60529 IP69 IP69K
NEMA degree of protection	NEMA 13 NEMA 4X
IK degree of protection	IK05 conforming to EN 50102
Standards	GB 14048.5 UL 508 EN/IEC 60947-5-1 CSA C22.2 No 14 JIS C8201-5-1 EN/IEC 60947-1 EN/IEC 60947-5-4 JIS C8201-1
Product Certifications	UL Listed CSA BV GL LROS (Lloyds register of shipping) DNV
Vibration resistance	5 gn 2500 Hz)IEC 60068-2-6
Shock resistance	30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27

# Ordering and shipping details

Category	US10CS222467
Discount Schedule	0CS2
GTIN	3389110666861
Returnability	No
Country of origin	FR

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.1 in (5.4 cm)
Package 1 Width	1.7 in (4.4 cm)
Package 1 Length	3.5 in (8.8 cm)
Package 1 Weight	1.2 oz (33.0 g)
Unit Type of Package 2	S02

Number of Units in Package 2	40
Package 2 Height	5.9 in (15.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	3.913 lb(US) (1.775 kg)

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>⊘</b>	Reach Free Of Svhc	
<b>②</b>	Toxic Heavy Metal Free	
<b>⊘</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Sep 10, 2024