Product data sheet

Specifications





Head for illuminated double headed push button, Harmony XB5, 2 white flush, 22mm, black marked + and -

ZB5AW7A1715

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 74.25 USD

Main

Range of Product	Harmony XB5	
Product or Component Type	Head for illuminated double-headed push-button	
Product Compatibility	Integral LED	
Device short name	ZB5	
Bezel material	Dark grey plastic	
Head type	Standard	
Mounting diameter	0.9 in (22 mm)	
Sale per indivisible quantity	1	
Shape of signaling unit head	Rectangular	
Type of operator	spring return	
Operator profile	2 flush push-buttons - 1 central pilot light	
Operators description	White "+" - white "-"	

Complementary

CAD overall width	1.2 in (30 mm)	
CAD overall height	2.0 in (50 mm)	
CAD overall depth	1.2 in (30 mm)	
Net Weight	0.051 lb(US) (0.023 kg)	
Colour of marking	Black marking when white caps	
Operator profile	White flush, + black) White flush, - black)	
Mechanical durability	1000000 cycles	
Station name	XALD 1 cut-out	
Device presentation	Basic sub-assemblies	

Environment

Ambient Air Temperature for Storage	-40.000000000158.0000000000 °F (-4070 °C)
Ambient Air Temperature for Operation	-13.000000000158.0000000000 °F (-2570 °C)
Electrical shock protection class	Class II IEC 60536

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

IP degree of protection	IP66 IP67 IP69 IP69K
NEMA degree of protection	NEMA 13 NEMA 4X
Resistance to high pressure washer	1015.3 psi (7000000 Pa) 131.0000000000 °F (55 °C) 0.1 m
IK degree of protection	IK05 conforming to IEC 50102
Standards	EN/IEC 60947-5-4 UL 508 CSA C22.2 No 14 EN/IEC 60947-5-1 JIS C8201-5-1 EN/IEC 60947-1 JIS C8201-1
Product Certifications	UL Listed CSA BV GL DNV LROS (Lloyds register of shipping)
Vibration resistance	5 gn 2500 Hz)IEC 60068-2-6
Shock resistance	30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27

Ordering and shipping details

Category	US10CS222467
Discount Schedule	0CS2
GTIN	3389119043403
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.8 in (4.5 cm)
Package 1 Width	1.3 in (3.3 cm)
Package 1 Length	2.09 in (5.3 cm)
Package 1 Weight	0.8 oz (23.0 g)

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

Certifications & Standards

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information