# Product data sheet

Specification





Head for illuminated double headed push button, Harmony XB5, 2 white black flush, 22mm, 1 central pilot light, marked up down arrow

ZB5AW7A1724

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 49.50 USD

#### Main

Range of Product	Harmony XB5	
Product or Component Type	Head for illuminated double-headed push-button	
Product Compatibility	Integral LED	
Device short name	ZB5	
Bezel material	Dark grey plastic	
Head type	Standard	
Mounting diameter	0.9 in (22 mm)	
Sale per indivisible quantity	1	
Shape of signaling unit head	Rectangular	
Type of operator	spring return	
Operator profile	2 flush push-buttons - 1 central pilot light	
Operators description	White "up arrow" - black "down arrow"	

# Complementary

	•	
CAD overall width	1.2 in (30 mm)	
CAD overall height	2.0 in (50 mm)	
CAD overall depth	1.2 in (30 mm)	
Net Weight	0.051 lb(US) (0.023 kg)	
Colour of marking	Black marking when white caps	
Operator profile	White flush, up arrow black) Black flush, down arrow white)	
Mechanical durability	1000000 cycles	
Station name	XALD 1 cut-out	
device presentation	Basic sub-assemblies	

#### **Environment**

Ambient Air Temperature for Storage	-40.0000000000158.0000000000 °F (-4070 °C)
Ambient Air Temperature for	-13.0000000000158.0000000000 °F (-2570 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Electrical shock protection class	Class II IEC 60536
IP degree of protection	IP66 IP67 IP69 IP69K
NEMA degree of protection	NEMA 13 NEMA 4X
Resistance to high pressure washer	1015.3 psi (7000000 Pa) 131.0000000000 °F (55 °C) 0.1 m
K degree of protection IK05 conforming to IEC 50102	
Standards	IEC 60947-1 UL 508 JIS C8201-5-1 IEC 60947-5-4 CSA C22.2 No 14 IEC 60947-5-1 JIS C8201-1
Product Certifications	BV CSA DNV GL UL Listed LROS (Lloyds register of shipping)
Vibration resistance	5 gn 2500 Hz)IEC 60068-2-6
Shock resistance	30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27

# Ordering and shipping details

Category	US10CS222467
Discount Oaks dada	
Discount Schedule	0CS2
GTIN	3389119603478
Returnability	No
Country of origin	FR

# **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.378 in (3.500 cm)	
Package 1 Width	1.772 in (4.500 cm)	
Package 1 Length	1.969 in (5.000 cm)	
Package 1 Weight	0.882 oz (25.000 g)	
Unit Type of Package 2	S01	
Number of Units in Package 2	50	
Package 2 Height	5.906 in (15.000 cm)	
Package 2 Width	5.906 in (15.000 cm)	
Package 2 Length	15.748 in (40.000 cm)	
Package 2 Weight	3.084 lb(US) (1.399 kg)	
Unit Type of Package 3	P06	
Number of Units in Package 3	1600	
Package 3 Height	29.528 in (75.000 cm)	

Package 3 Width	31.496 in (80.000 cm)
Package 3 Length	23.622 in (60.000 cm)
Package 3 Weight	116.334 lb(US) (52.768 kg)

# **Contractual warranty**

Warranty 18 months



**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

# Well-being performance

<b>②</b>	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
<b>②</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes


### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information


# **Dimensions Drawings**

#### **Dimensions**

#### **Without Boot**



#### With Boot ZBA708




# **Product data sheet**

# ZB5AW7A1724

**Technical Description** 

**Electrical Composition Corresponding to Codes M1 and M7** 



# **Electrical Composition Corresponding to Codes M2 and M8**



# **Electrical Composition Corresponding to Codes M6 and P2**



# Electrical Composition Corresponding to Codes M5, M10, MF1, MR1 and MF2



# Legend

Single contact



Double contact



Light block



Possible location

