Product data sheet

Specifications

Green Premium™



Head for illuminated double headed push button, Harmony XB5, 2 flush whitout cap, 22mm, 1 central pilot light, unmarked

ZB5AW7A9

Main

Range of product	Harmony XB5	
Product or component type	Head for illuminated double-headed push-button	
Product compatibility	Integral LED	
Device short name	ZB5	
Bezel material	Dark grey plastic	
Head type	Standard	
Mounting diameter	0.9 in (22 mm)	
Sale per indivisible quantity	1	
Shape of signaling unit head	Rectangular	
Type of operator	spring return	
Operator profile	2 flush push-buttons - 1 central pilot light	
Operators description	Black pushes without cap	

Complementary

CAD overall width	1.2 in (30 mm)
CAD overall height	2.0 in (50 mm)
CAD overall depth	1.2 in (30 mm)
Net weight	0.051 lb(US) (0.023 kg)
Operator profile	without cap
Mechanical durability	1000000 cycles
Station name	XALD 1 cut-out
Device presentation	Basic sub-assemblies

Environment

Ambient air temperature for storage	-40.000000000158.0000000000 °F (-4070 °C)	
Ambient air temperature for operation	-13.000000000158.000000000 °F (-2570 °C)	
Electrical shock protection class	Class II IEC 60536	
IP degree of protection	IP66 IP67 IP69 IP69K	
NEMA degree of protection	NEMA 13 NEMA 4X	

1015.3 psi (700000 Pa) 131.000000000 °F (55 °C) 0.1 m IK05 conforming to IEC 50102 UL 508 JIS C8201-5-1 EN/IEC 60947-5-4 CSA C22.2 No 14 EN/IEC 60947-5-1
UL 508 JIS C8201-5-1 EN/IEC 60947-5-4 CSA C22.2 No 14
JIS C8201-5-1 EN/IEC 60947-5-4 CSA C22.2 No 14
EN/IEC 60947-5-4 CSA C22.2 No 14
CSA C22.2 No 14
EN/IEC 60947-1
JIS C8201-1
JIS C8201-1
BV
UL listed
CSA
LROS (Lloyds register of shipping)
DNV
GL
5 gn 2500 Hz)IEC 60068-2-6
30 gn 18 ms) half sine wave acceleration IEC 60068-2-27

Packing Units

CE
102 in (2.800 cm)
890 in (4.800 cm)
890 in (4.800 cm)
847 oz (24.000 g)
B1
205 in (5.600 cm)
378 in (3.500 cm)
0.433 in (26.500 cm)
303 oz (122.000 g)
02
)
906 in (15.000 cm)
1.811 in (30.000 cm)
5.748 in (40.000 cm)
333 lb(US) (1.512 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

Certifications & Standards


Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Product data sheet

Dimensions Drawings

Dimensions

Without Boot



With Boot ZBA708

