Product data sheet

Specification





yellow square flush pushbutton head Ø22 spring return unmarked

ZB5CA5

- Discontinued on: Dec 2, 2020
- ! End-of-service on: Dec 31, 2020

① Discontinued

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	Harmony XB5	
Product or Component Type	Head for non-illuminated push-button	
Device short name	ZB5	
Bezel material	Dark grey plastic	
Mounting diameter	0.9 in (22 mm)	
Head type	Standard	
Sale per indivisible quantity	1	
Shape of signaling unit head	Square	
Type of operator	spring return	
Operator profile	Yellow flush, unmarked	

Complementary

CAD overall width	1.2 in (30 mm)	
	1.2 III (30 11111)	
CAD overall height	1.2 in (30 mm)	
CAD overall depth	1.1 in (28 mm)	
Net Weight	0.042 lb(US) (0.019 kg)	
Mechanical durability	5000000 cycles	
Station name	XALD 15 cut-outs	
	XALK 25 cut-outs	
Electrical composition code	C1 9 single front mounting	
	C2 9 single and double front mounting	
	C11 3 single front mounting	
	C15 1 single front mounting	
	SF1 3 single front mounting	
	SR1 3 single rear mounting	
Device presentation	Basic element	

Environment

protective treatment	тн	
Ambient Air Temperature for Storage	-40.0000000000158.0000000000 °F (-4070 °C)	
Ambient Air Temperature for Operation	-13.0000000000158.00000000000 °F (-2570 °C)	
Overvoltage category	Class II IEC 60536	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

IP degree of protection	IP66 IEC 60529 NEMA 13 NEMA 4X	
NEMA degree of protection		
Resistance to high pressure washer	1015.3 psi (7000000 Pa) 131.0000000000 °F (55 °C) 0.1 m	
IK degree of protection	IK03 conforming to IEC 50102	
Product Certifications	BV CSA GL DNV LROS (Lloyds register of shipping) UL Listed	
Shock resistance	30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27	
Vibration resistance	5 gn 2500 Hz)IEC 60068-2-6	

Ordering and shipping details

Category	US10CS222467	
Discount Schedule	0CS2	
GTIN	3389110925937	
Returnability	No	
Country of origin	FR	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.1 in (5.4 cm)	
Package 1 Width	1.3 in (3.4 cm)	
Package 1 Length	1.7 in (4.4 cm)	
Package 1 Weight	0.7 oz (19 g)	

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Reach Free Of Svhc	
②	Toxic Heavy Metal Free	
⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov