


Product data sheet

Specifications



Antimicrobial plain cap, Harmony XB5, Harmony XB4, green, for flush mounted push button

ZBAF3

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 4.11 USD

Main

accessory / separate part category	Marking accessory
accessory / separate part type	Blank push-button cap
Product or Component Type	Antimicrobial plain cap
Product Compatibility	ZB4FA0 ZB5FA0
accessory / separate part destination	Push-button head
Cap/operator or lens colour	Green
Shape of signaling unit head	Round
Quantity per Set	Set of 1
Sale per indivisible quantity	10
Net Weight	0.002 lb(US) (0.001 kg)

Complementary

Range Compatibility	Harmony XAL Harmony XB5 Harmony XB4
Operator profile	Flush
Main group	Push-button Selector switch

Environment

Standards	ISO 21702 ISO 22196:2011
-----------	-----------------------------

Ordering and shipping details

Category	US10CS222467
Discount Schedule	0CS2
GTIN	3606481340696
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of Units in Package 1	1
Package 1 Height	0.591 in (1.500 cm)
Package 1 Width	0.984 in (2.500 cm)
Package 1 Length	0.984 in (2.500 cm)
Package 1 Weight	0.071 oz (2.000 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	1.772 in (4.500 cm)
Package 2 Width	2.165 in (5.500 cm)
Package 2 Length	2.165 in (5.500 cm)
Package 2 Weight	0.882 oz (25.000 g)
Unit Type of Package 3	S02
Number of Units in Package 3	450
Package 3 Height	5.906 in (15.000 cm)
Package 3 Width	11.811 in (30.000 cm)
Package 3 Length	15.748 in (40.000 cm)
Package 3 Weight	3.012 lb(US) (1.366 kg)

Sustainability





Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	Yes
Reach Regulation		REACH Declaration
Eu Rohs Directive		Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation		China RoHS declaration
California Proposition 65		"WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov "

Offer Marketing Illustration

Product benefits / Features

Features

Harmony XB5



Quick and easy assembly and disassembly



Excellent mechanical connection with operator head



Various types of connection: screw clamp, connector, Faston connector, spring terminal, or printed circuit board



Large set of accessories to customize your panels



Robustness to withstand harsh environments



Offer Marketing Illustration

Product benefits / Features

Technical Benefits

Harmony XB5

Conformity with IEC, UL, CSA, CCC EAC, and JIS standards, as well as CE marking and marine approvals

Up to IP66, 67, 69, 69K, and type 4X protection ratings

High vibration resistance with shake-proof terminal screws

Operating temperature from -40°C –to 70°C

Shock protection level up to IK06

Secure switching of inductive or heavy DC loads directly – 100 000 operations at 10A, 24V dc



Image of product / Alternate images

Alternative

