

# ZCKE676

Limit switch head, Limit switches XC Standard, ZCKE, steel roller plunger reinforced, -40 Â°C



## Main

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product           | Telemecanique Limit switches XC Standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Series name                | Standard format                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Product or component type  | Limit switch head                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Device short name          | ZCKE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Head type                  | Plunger head                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Product compatibility      | XCKJ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Associated body            | ZCKJ2H29<br>ZCKJ8H7<br>ZCKJ7H29<br>ZCKJD31<br>ZCKJD37H7<br>ZCKJD31H7<br>ZCKJ6H29<br>ZCKJ6H7<br>ZCKJ4H7<br>ZCKJ6<br>ZCKJ5H29<br>ZCKJ9H7<br>ZCKJ1H29<br>ZCKJ1H7<br>ZCKJ9H29<br>ZCKJ41H7<br>ZCKJ2H7<br>ZCKJ41H29<br>ZCKJ4<br>ZCKJD39H7<br>ZCKJ4H29<br>ZCKJD31H29<br>ZCKJD35H29<br>ZCKJ5H7<br>ZCKJ41<br>ZCKJD35H7<br>ZCKJ5<br>ZCKJD37H29<br>ZCKJ7<br>ZCKJD39H29<br>ZCKJD35<br>ZCKJ8<br>ZCKJD37<br>ZCKJ21H29<br>ZCKJ7H7<br>ZCKJ21H7<br>ZCKJ21<br>ZCKJD39<br>ZCKJ9<br>ZCKJ8H29<br>ZCKJ11H29<br>ZCKJ11H7<br>ZCKJ1<br>ZCKJ2<br>ZCKJ11 |
| Movement of operating head | Linear                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Type of operator           | Roller plunger spring return metal (reinforced)                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Type of approach           | Lateral approach, 2 directions                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

## Complementary

|                  |            |
|------------------|------------|
| Switch actuation | By 30° cam |
| Positive opening | With       |
| Net weight       | 0.155 kg   |
| Head material    | Metal      |

## Environment

|                                       |                 |
|---------------------------------------|-----------------|
| Ambient air temperature for operation | -40...70 °C     |
| Ambient air temperature for storage   | -40...70 °C     |
| Environmental characteristic          | Low temperature |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 4.200 cm  |
| Package 1 Width              | 9.000 cm  |
| Package 1 Length             | 4.700 cm  |
| Package 1 Weight             | 160.000 g |
| Unit Type of Package 2       | S01       |
| Number of Units in Package 2 | 24        |
| Package 2 Height             | 15.000 cm |
| Package 2 Width              | 15.000 cm |
| Package 2 Length             | 40.000 cm |
| Package 2 Weight             | 4.112 kg  |

## Offer Sustainability

|                                            |                                                                                                                                                                                                                                                                                             |
|--------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status                   | Green Premium product                                                                                                                                                                                                                                                                       |
| Circularity Profile                        | No need of specific recycling operations                                                                                                                                                                                                                                                    |
| California proposition 65                  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| For all Reach Rohs enquiries contact us at | <a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>                                                                                                                                                                                                              |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|