



PRODUCT-DETAILS

ZLS972
DIN Adapter



General Information	
Extended Product Type	ZLS972
Product ID	2CCA180555R0001
EAN	7612271444709
Catalog Description	DIN Adapter
Long Description	DIN adapter use for SMISLINE TP system 125A or 250A. Wire top feed moveable for L1 or L2 or L3

Technical	
Number of DIN Rails for Mounting	1

Electrical	
Rated Operational Voltage	Acc. to IEC 690 V AC 440 V DC
Rated Current (I _n)	63 A

Material Compliance

RoHS Information	9AKK107991A9646
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20170426
REACH Declaration	9AKK108467A9561
REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20230417
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business

Environmental

Environmental Information	9AKK108467A9561
---------------------------	-----------------

Dimensions

Product Net Width	18 mm
Product Net Height	87 mm
Product Net Depth / Length	13 mm
Product Net Weight	24 g
Dimension Diagram	9AKK107492A6192

Ordering

Package Level 1 Units	carton 1 piece
Package Level 1 Gross Weight	240 g
E-Number (Norway)	1683009
E-Number (Switzerland)	809996107

Certificates and Declarations

Declaration of Conformity - CE	9AKK107991A9646
--------------------------------	-----------------

Installation

Instructions and Manuals	2CCR818148B0001
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	9AKK107492A6192
-----------------------------------	-----------------

External Classifications and Standards

ETIM 9	EC001531 - Busbar adapter
UNSPSC	39122221
eClass	V11.0 : 27370304

IDEA Granular Category Code (IGCC)	5219 >> Switch part or accessory
Object Classification Code	X
Standards	IEC/EN 61439-6 UL508

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Plug-in Distribution Systems → Plug-in Distribution Systems
Accessories → Adapters and Combi Modules



360°