


## Subminiature Basic Switch








## D3M

Saves Wiring Effort, Production Steps, and Time

- Easy wiring ensured through the Quick-Connect Terminals
- External actuator mounts in either of two directions
- Horizontal layout of terminals saves mounting space
- Same internal mechanism as the OMRON SS Subminiature Basic Switch



## Ordering Information

Actuator	Actuator mounting position		Contact type	Part number
Pin plunger	---		SPST-NC	D3M-01
			SPST-NO	D3M-01-3
Hinge lever	K		SPST-NC	D3M-01K1
			SPST-NO	D3M-01K1-3
	L		SPST-NC	D3M-01L1
			SPST-NO	D3M-01L1-3
Hinge roller lever	K		SPST-NC	D3M-01K2
			SPST-NO	D3M-01K2-3
	L		SPST-NC	D3M-01L2
			SPST-NO	D3M-01L2-3
Simulated hinge lever	K		SPST-NC	D3M-01K3
			SPST-NO	D3M-01K3-3
	L		SPST-NC	D3M-01L3
			SPST-NO	D3M-01L3-3

## MODEL NUMBER LEGEND


D3M-01      

1    2    3


### 1. Actuator Mounting Position

None: No actuator

K: Pushbutton close to actuator fulcrum



L: Pushbutton far from actuator fulcrum



### 2. Actuator Type

None: Pin plunger

1: Hinge lever

2: Hinge roller lever

3: Simulated hinge lever

### 3. Contact Specification

None: SPST-NC (with red pushbutton)

-3: SPST-NO (with black pushbutton)

## CONNECTORS


Refer to *Wiring* on page 8 for details.

# Specifications

## RATINGS

Rated voltage	Resistive load
30 VDC	0.1 A

Use the D3M in the following permissible operating range.



### Minimum Applicable Load (Level N)

Voltage	Resistive load
5 VDC	1 mA

Refer to *Minimum Load* on page 8 for details.

## APPROVED STANDARDS


EN61058-1

UL1054


CSA C22.2 No.55

## ■ CONTACT FORM

SPST-NC



SPST-NO



## ■ CHARACTERISTICS

Permissible operating speed (see note 1)		0.1 mm/s to 1 m/s
Permissible operating frequency	Mechanical	400 operations/min max.
	Electrical	60 operations/min max.
Insulation resistance		100 M $\Omega$ min. at 500 VDC
Contact resistance (initial value)		100 m $\Omega$ max. including connector and 50-mm AWG28 lead wire resistance
Dielectric strength	Between terminals of the same polarity	1,000 VAC at 50/60 Hz for 1 min
	Between charged metal part and ground	1,500 VAC at 50/60 Hz for 1 min
	Between non-charged metal part and each terminal	1,500 VAC at 50/60 Hz for 1 min
Vibration resistance	Malfunction (See Note 2.)	10 to 55 Hz, 1.5-mm double amplitude for 1 ms max. with contacts closed or open.
Shock resistance	Destruction	1,000 m/s <sup>2</sup> (approx. 100G)
	Malfunction (See Note 2.)	300 m/s <sup>2</sup> (approx. 30G) for 1 ms max. with contacts closed or open.
Life expectancy	Mechanical	500,000 operations (at full-stroke operating speed of 10 mm/s at a frequency of 60 operations/min)
	Electrical	200,000 times (at full-stroke operating speed of 10 mm/s at a frequency of 30 operations/min)
Enclosure rating		IP00
Degree of protection against electric shock		Class I
Proof tracking index (PTI)		175
Ambient temperature	Operating	-25°C to 85°C (with no icing)
Ambient humidity	Operating	85% max.
Weight		Approx. 2 g (pin plunger model)

Note: 1. The permissible operating speed applies to pin plunger models.

2. If a lever actuator model is used, the above vibration resistance conditions will apply when the actuator is in the maximum over-travel position.

## ■ CONTACT SPECIFICATIONS


Contact	Cross bar
Material	Gold alloy
Distance between contacts	0.5 mm

## Dimensions


Unit: mm (inch)

## ■ MOUNTING DIMENSIONS FOR ALL MODELS

Use M2.3 screws, flat washers, and spring washers to mount the D3M securely. Make sure that the tightening torque applied to each screw is within a range from 2.3 to 2.7 kgf • cm.




## ■ PIN PLUNGER MODELS



Operating Characteristics	D3M-01, D3M-01-3
Max. operating force (OF)	153 gf
Min. reset force (RF)	25 gf
Min. pretravel (PT)	0.6 mm
Min. overtravel (OT)	0.4 mm
Max. movement differential (MD)	0.1 mm
Operating position (OP)	8.4±0.3 mm


## HINGE LEVER MODELS



Operating Characteristics	D3M-01K1, D3M-01K1-3
Max. operating force (OF)	51 gf
Min. reset force (RF)	6 gf
Min. overtravel (OT)	1.2 mm
Max. movement differential (MD)	0.8 mm
Max. free position (FP)	14.0 mm
Operating position (OP)	10.0±0.8 mm


Note: 1. A tolerance of  $\pm 0.4$  mm applies to all of the above dimensions unless otherwise specified.

2. The operating characteristics apply when each actuator is moved in the direction indicated by the arrow and "A."



Operating Characteristics	D3M-01L1, D3M-01L1-3
Max. operating force (OF)	102 gf
Min. reset force (RF)	10 gf
Min. overtravel (OT)	0.7 mm
Max. movement differential (MD)	0.6 mm
Max. free position (FP)	11.5 mm
Operating position (OP)	9.2±0.6 mm

## HINGE ROLLER LEVER MODELS




- Note: 1. The terminals connect to JST's Dipole XA Connector.
2. The Dipole XA Connector consists of the following components.  
Contact: SAX-001T-P0.6  
Housing: XAP-02V-1(13)

Operating Characteristics	D3M-01K2, D3M-01J2-3
Max. operating force (OF)	51 gf
Min. reset force (RF)	6 gf
Min. overtravel (OT)	1.2 mm
Max. movement differential (MD)	0.8 mm
Max. free position (FP)	19.7 mm
Operating position (OP)	15.7±0.8 mm

Note: 1. A tolerance of ±0.4 mm applies to all of the above dimensions unless otherwise specified.


2. The operating characteristics apply when each actuator is moved in the direction indicated by the arrow and "A."



- Note: 1. The terminals connect to JST's Dipole XA Connector.
2. The Dipole XA Connector consists of the following components.  
Contact: SAX-001T-P0.6  
Housing: XAP-02V-1(13)

Operating Characteristics	D3M-01L2, D3M-01L2-3
Max. operating force (OF)	102 gf
Min. reset force (RF)	10 gf
Min. overtravel (OT)	0.7 mm
Max. movement differential (MD)	0.6 mm
Max. free position (FP)	17.2 mm
Operating position (OP)	14.9±0.6 mm


## SIMULATED HINGE LEVER MODELS



- Note: 1. The terminals connect to JST's Dipole XA Connector.  
2. The Dipole XA Connector consists of the following components.  
Contact: SAX-001T-P0.6  
Housing: XAP-02V-1 (13)

Operating Characteristics	D3M-01K3, D3M-01K3-3
Max. operating force (OF)	51 gf
Min. reset force (RF)	6 gf
Min. overtravel (OT)	1.2 mm
Max. movement differential (MD)	0.8 mm
Max. free position (FP)	16.2 mm
Operating position (OP)	12.2±0.8 mm

Note: 1. A tolerance of  $\pm 0.4$  mm applies to all of the above dimensions unless otherwise specified.  
2. The operating characteristics apply when each actuator is moved in the direction indicated by the arrow and "A."



- Note: 1. The terminal's connect to JST's Dipole XA Connector.
2. The Dipole XA Connector consists of the following components.  
Contact: SAX-001T-P0.6  
Housing: XAP-02V-1(13)

Operating Characteristics	D3M-01L3, D3M-01L3-3
Max. operating force (OF)	102 gf
Min. reset force (RF)	10 gf
Min. overtravel (OT)	0.7 mm
Max. movement differential (MD)	0.6 mm
Max. free position (FP)	13.6 mm
Operating position (OP)	11.3±0.6 mm

Note: 1. A tolerance of  $\pm 0.4$  mm applies to all of the above dimensions unless otherwise specified.  
2. The operating characteristics apply when each actuator is moved in the direction indicated by the arrow and "A."

## Precautions

### ■ MOUNTING

To avoid an electric shock or a fire, be sure to turn OFF the D3M before mounting, removing, wiring, or servicing.

Make sure that the surface to which the D3M is mounted is flat. If the surface is not flat, the housing may distort, and the D3M may malfunction, or the housing may crack.

### ■ OPERATING STROKE

Make sure that the dog is separated from the actuator when the actuator is in the free position and that the actuator is pressed appropriately when the D3M is actuated. The actuator must not be pressed excessively to reach the maximum overtravel position, or the D3M may be damaged.

Make sure the actuator is pressed in the direction where the D3M is actuated.

### ■ MINIMUM LOAD

If the load causes inrush current, even though the D3M is in operation within the permissible operating range, the life of the D3M may be shortened. In this case, insert a contact protection circuit.

The minimum applicable load is on the basis of level N, that is, a reliable rate of 60% ( $\lambda 60$ ), in accordance with JIS C5003.

This rate ( $\lambda 60 = 0.5 \times 10^{-6}$ /operations) means that the D3M is expected to have operational failure at least once per 2,000,000 operations.

### ■ WIRING

The terminals connect to JST's Dipole XA Connector.

The Dipole XA Connector consists of the following components.

Contact: SAX-001T-P0.6

Housing: XAP-02V-1

OMRON does not sell the Dipole XA Connector. Contact the following.

J. S. T. Corporation (U.S.A.)

Tel: (1)847-473-1957

Fax: (1)847-473-0144



#### Caution

The voltage and current applied to the D3M must be within the rated ranges when it is turned ON, turned OFF, and in operation, or the service life of the D3M may be shortened. Also note that if inappropriate voltage and current are applied, the D3M may radiate heat and burn.

**NOTE: DIMENSIONS SHOWN ARE IN MILLIMETERS. To convert millimeters to inches divide by 25.4.**

# OMRON®

OMRON ELECTRONICS, INC.

One East Commerce Drive

Schaumburg, IL 60173

1-800-55-OMRON

OMRON CANADA, INC.

885 Milner Avenue

Scarborough, Ontario M1B 5V8

416-286-6465