Representative Image

Catalog No. 9342SST6

Description: SST6 1/2 in. 45, M20

UPC No 5415022502633

Home > Cable Protection Systems > T&B Liquidtight Fittings > Liquid tight connectors

Liguid-tight 45 Degree Fitting, Trade Size 1/2 Inch, M20 Thread, 316 Stainless with Zinc Plated Steel Ground Cone

Descriptors

Category	Liquid tight connectors

Specifications

Material	316 Stainless Steel
Color	Metallic
NEMA Rating	Type 3, 3R, 4, 4X, 12, 13
Temperature Rating	UL: -4 to 221 F

Classifications

Brand Name	T&B Liquidtight Fittings
Standard	UL E23018 , CSA LR-4484 , IEC/EN 61386-1, -23

Dimensions

Size	1/2 Inch , M20 Thread

Compliance and Certifications

RoHS	RoHS3 Compliant

ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	1/2 inch
Degree of protection (IP) conduit dependant	66-67
Model	45°-Bend
Revolving thread	N
Construction type	External thread
Connection type screw connection to housing	Thread
Thread type	Metric
Thread connection size	M50 x 1.5

ETIM	EC001180 Screw connection for protective metallic hose
Material housing	Stainless steel
Approved in combination with protective conduit DIN EN 61386-23	Y
Approved in combination with protective conduit CSA	Y
Approved in combination with protective conduit UL	Y
Working temperature	-20 - +105 °C
Working temperature	-4 - +221 °F

Certification/Standard

CLASS	File Number	Class	CCN	Certificate Number	Library Number
CSA	4484	441202	N/A	N/A	N/A
UL	E23018	N/A	DWTT	N/A	N/A